

Network Working Group
Request for Comments: 1907
Obsoletes: 1450
Category: Standards Track

SNMPv2 Working Group
J. Case
SNMP Research, Inc.
K. McCloghrie
Cisco Systems, Inc.
M. Rose
Dover Beach Consulting, Inc.
S. Waldbusser
International Network Services
January 1996

Management Information Base
for Version 2 of the
Simple Network Management Protocol (SNMPv2)

Status of this Memo

This document specifies an Internet standards track protocol for the Internet community, and requests discussion and suggestions for improvements. Please refer to the current edition of the "Internet Official Protocol Standards" (STD 1) for the standardization state and status of this protocol. Distribution of this memo is unlimited.

Table of Contents

1. Introduction	2
1.1 A Note on Terminology	2
2. Definitions	2
2.1 The System Group	3
2.2 The SNMP Group	7
2.4 Information for Notifications	9
2.4.1 Well-known Traps	10
2.5 The Set Group	11
2.6 Conformance Information	11
2.6.1 Compliance Statements	11
2.6.2 Units of Conformance	12
2.6.3 Obsolete Definitions	13
3. Security Considerations	18
4. Editor's Address	19
5. Acknowledgements	19
6. References	20

1. Introduction

A management system contains: several (potentially many) nodes, each with a processing entity, termed an agent, which has access to management instrumentation; at least one management station; and, a management protocol, used to convey management information between the agents and management stations. Operations of the protocol are carried out under an administrative framework which defines authentication, authorization, access control, and privacy policies.

Management stations execute management applications which monitor and control managed elements. Managed elements are devices such as hosts, routers, terminal servers, etc., which are monitored and controlled via access to their management information.

Management information is viewed as a collection of managed objects, residing in a virtual information store, termed the Management Information Base (MIB). Collections of related objects are defined in MIB modules. These modules are written using a subset of OSI's Abstract Syntax Notation One (ASN.1) [1], termed the Structure of Management Information (SMI) [2].

The management protocol, SNMPv2 [3], provides for the exchange of messages which convey management information between the agents and the management stations. It is the purpose of this document to define managed objects which describe the behavior of a SNMPv2 entity.

1.1. A Note on Terminology

For the purpose of exposition, the original Internet-standard Network Management Framework, as described in RFCs 1155 (STD 16), 1157 (STD 15), and 1212 (STD 16), is termed the SNMP version 1 framework (SNMPv1). The current framework is termed the SNMP version 2 framework (SNMPv2).

2. Definitions

```
SNMPv2-MIB DEFINITIONS ::= BEGIN
```

```
IMPORTS
```

```
    MODULE-IDENTITY, OBJECT-TYPE, NOTIFICATION-TYPE,  
    TimeTicks, Counter32, snmpModules, mib-2  
        FROM SNMPv2-SMI  
    DisplayString, TestAndIncr, TimeStamp  
        FROM SNMPv2-TC  
    MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP  
        FROM SNMPv2-CONF;
```

snmpMIB MODULE-IDENTITY

LAST-UPDATED "9511090000Z"
ORGANIZATION "IETF SNMPv2 Working Group"
CONTACT-INFO

" Marshall T. Rose

Postal: Dover Beach Consulting, Inc.
420 Whisman Court
Mountain View, CA 94043-2186
US

Tel: +1 415 968 1052

E-mail: mrose@dbc.mtview.ca.us"

DESCRIPTION

"The MIB module for SNMPv2 entities."

REVISION "9304010000Z"

DESCRIPTION

"The initial revision of this MIB module was published as
RFC 1450."

::= { snmpModules 1 }

snmpMIBObjects OBJECT IDENTIFIER ::= { snmpMIB 1 }

-- ::= { snmpMIBObjects 1 } this OID is obsolete
-- ::= { snmpMIBObjects 2 } this OID is obsolete
-- ::= { snmpMIBObjects 3 } this OID is obsolete

-- the System group

--

-- a collection of objects common to all managed systems.

system OBJECT IDENTIFIER ::= { mib-2 1 }

sysDescr OBJECT-TYPE

SYNTAX DisplayString (SIZE (0..255))

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A textual description of the entity. This value should
include the full name and version identification of the
system's hardware type, software operating-system, and
networking software."

::= { system 1 }

sysObjectID OBJECT-TYPE

```
SYNTAX      OBJECT IDENTIFIER
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The vendor's authoritative identification of the network
    management subsystem contained in the entity. This value is
    allocated within the SMI enterprises subtree (1.3.6.1.4.1)
    and provides an easy and unambiguous means for determining
    'what kind of box' is being managed. For example, if vendor
    'Flintstones, Inc.' was assigned the subtree
    1.3.6.1.4.1.4242, it could assign the identifier
    1.3.6.1.4.1.4242.1.1 to its 'Fred Router'."
 ::= { system 2 }

sysUpTime OBJECT-TYPE
SYNTAX      TimeTicks
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The time (in hundredths of a second) since the network
    management portion of the system was last re-initialized."
 ::= { system 3 }

sysContact OBJECT-TYPE
SYNTAX      DisplayString (SIZE (0..255))
MAX-ACCESS  read-write
STATUS      current
DESCRIPTION
    "The textual identification of the contact person for this
    managed node, together with information on how to contact
    this person. If no contact information is known, the value
    is the zero-length string."
 ::= { system 4 }

sysName OBJECT-TYPE
SYNTAX      DisplayString (SIZE (0..255))
MAX-ACCESS  read-write
STATUS      current
DESCRIPTION
    "An administratively-assigned name for this managed node.
    By convention, this is the node's fully-qualified domain
    name. If the name is unknown, the value is the zero-length
    string."
 ::= { system 5 }

sysLocation OBJECT-TYPE
SYNTAX      DisplayString (SIZE (0..255))
MAX-ACCESS  read-write
```

```

STATUS      current
DESCRIPTION
    "The physical location of this node (e.g., 'telephone
    closet, 3rd floor').  If the location is unknown, the value
    is the zero-length string."
 ::= { system 6 }

```

sysServices OBJECT-TYPE

```

SYNTAX      INTEGER (0..127)
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "A value which indicates the set of services that this
    entity may potentially offers.  The value is a sum.  This
    sum initially takes the value zero, Then, for each layer, L,
    in the range 1 through 7, that this node performs
    transactions for, 2 raised to (L - 1) is added to the sum.
    For example, a node which performs only routing functions
    would have a value of 4 (2^(3-1)).  In contrast, a node
    which is a host offering application services would have a
    value of 72 (2^(4-1) + 2^(7-1)).  Note that in the context
    of the Internet suite of protocols, values should be
    calculated accordingly:

```

layer	functionality
1	physical (e.g., repeaters)
2	datalink/subnetwork (e.g., bridges)
3	internet (e.g., supports the IP)
4	end-to-end (e.g., supports the TCP)
7	applications (e.g., supports the SMTP)

```

    For systems including OSI protocols, layers 5 and 6 may also
    be counted."
 ::= { system 7 }

```

```
-- object resource information
```

```
--
```

```
-- a collection of objects which describe the SNMPv2 entity's
-- (statically and dynamically configurable) support of
-- various MIB modules.
```

sysORLastChange OBJECT-TYPE

```

SYNTAX      TimeStamp
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The value of sysUpTime at the time of the most recent

```

```
        change in state or value of any instance of sysORID."
 ::= { system 8 }

sysORTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF SysOREntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The (conceptual) table listing the capabilities of the
        local SNMPv2 entity acting in an agent role with respect to
        various MIB modules.  SNMPv2 entities having dynamically-
        configurable support of MIB modules will have a
        dynamically-varying number of conceptual rows."
 ::= { system 9 }

sysOREntry OBJECT-TYPE
    SYNTAX      SysOREntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry (conceptual row) in the sysORTable."
    INDEX       { sysORIndex }
 ::= { sysORTable 1 }

SysOREntry ::= SEQUENCE {
    sysORIndex      INTEGER,
    sysORID         OBJECT IDENTIFIER,
    sysORDescr     DisplayString,
    sysORUpTime    TimeStamp
}

sysORIndex OBJECT-TYPE
    SYNTAX      INTEGER (1..2147483647)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The auxiliary variable used for identifying instances of
        the columnar objects in the sysORTable."
 ::= { sysOREntry 1 }

sysORID OBJECT-TYPE
    SYNTAX      OBJECT IDENTIFIER
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "An authoritative identification of a capabilities statement
        with respect to various MIB modules supported by the local
        SNMPv2 entity acting in an agent role."
```

```
 ::= { sysOREntry 2 }

sysORDescr OBJECT-TYPE
    SYNTAX      DisplayString
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A textual description of the capabilities identified by the
         corresponding instance of sysORID."
    ::= { sysOREntry 3 }

sysORUpTime OBJECT-TYPE
    SYNTAX      TimeStamp
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The value of sysUpTime at the time this conceptual row was
         last instantiated."
    ::= { sysOREntry 4 }

-- the SNMP group
--
-- a collection of objects providing basic instrumentation and
-- control of an SNMP entity.

snmp      OBJECT IDENTIFIER ::= { mib-2 11 }

snmpInPkts OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The total number of messages delivered to the SNMP entity
         from the transport service."
    ::= { snmp 1 }

snmpInBadVersions OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The total number of SNMP messages which were delivered to
         the SNMP entity and were for an unsupported SNMP version."
    ::= { snmp 3 }

snmpInBadCommunityNames OBJECT-TYPE
    SYNTAX      Counter32
```

```
MAX-ACCESS read-only
STATUS      current
DESCRIPTION
    "The total number of SNMP messages delivered to the SNMP
    entity which used a SNMP community name not known to said
    entity."
 ::= { snmp 4 }

snmpInBadCommunityUses OBJECT-TYPE
SYNTAX      Counter32
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The total number of SNMP messages delivered to the SNMP
    entity which represented an SNMP operation which was not
    allowed by the SNMP community named in the message."
 ::= { snmp 5 }

snmpInASNParseErrs OBJECT-TYPE
SYNTAX      Counter32
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The total number of ASN.1 or BER errors encountered by the
    SNMP entity when decoding received SNMP messages."
 ::= { snmp 6 }

snmpEnableAuthenTraps OBJECT-TYPE
SYNTAX      INTEGER { enabled(1), disabled(2) }
MAX-ACCESS  read-write
STATUS      current
DESCRIPTION
    "Indicates whether the SNMP entity is permitted to generate
    authenticationFailure traps. The value of this object
    overrides any configuration information; as such, it
    provides a means whereby all authenticationFailure traps may
    be disabled.

    Note that it is strongly recommended that this object be
    stored in non-volatile memory so that it remains constant
    across re-initializations of the network management system."
 ::= { snmp 30 }

snmpSilentDrops OBJECT-TYPE
SYNTAX      Counter32
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
```



```

    "The total number of GetRequest-PDUs, GetNextRequest-PDUs,
    GetBulkRequest-PDUs, SetRequest-PDUs, and InformRequest-PDUs
    delivered to the SNMP entity which were silently dropped
    because the size of a reply containing an alternate
    Response-PDU with an empty variable-bindings field was
    greater than either a local constraint or the maximum
    message size associated with the originator of the request."
 ::= { snmp 31 }

snmpProxyDrops OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The total number of GetRequest-PDUs, GetNextRequest-PDUs,
        GetBulkRequest-PDUs, SetRequest-PDUs, and InformRequest-PDUs
        delivered to the SNMP entity which were silently dropped
        because the transmission of the (possibly translated)
        message to a proxy target failed in a manner (other than a
        time-out) such that no Response-PDU could be returned."
 ::= { snmp 32 }

-- information for notifications
--
-- a collection of objects which allow the SNMPv2 entity, when
-- acting in an agent role, to be configured to generate
-- SNMPv2-Trap-PDUs.

snmpTrap          OBJECT IDENTIFIER ::= { snmpMIBObjects 4 }

snmpTrapOID OBJECT-TYPE
    SYNTAX      OBJECT IDENTIFIER
    MAX-ACCESS  accessible-for-notify
    STATUS      current
    DESCRIPTION
        "The authoritative identification of the notification
        currently being sent. This variable occurs as the second
        varbind in every SNMPv2-Trap-PDU and InformRequest-PDU."
 ::= { snmpTrap 1 }

-- ::= { snmpTrap 2 }    this OID is obsolete

snmpTrapEnterprise OBJECT-TYPE
    SYNTAX      OBJECT IDENTIFIER
    MAX-ACCESS  accessible-for-notify
    STATUS      current
```

```
DESCRIPTION
    "The authoritative identification of the enterprise
    associated with the trap currently being sent.  When a
    SNMPv2 proxy agent is mapping an RFC1157 Trap-PDU into a
    SNMPv2-Trap-PDU, this variable occurs as the last varbind."
 ::= { snmpTrap 3 }

-- ::= { snmpTrap 4 }    this OID is obsolete

-- well-known traps

snmpTraps      OBJECT IDENTIFIER ::= { snmpMIBObjects 5 }

coldStart NOTIFICATION-TYPE
  STATUS current
  DESCRIPTION
    "A coldStart trap signifies that the SNMPv2 entity, acting
    in an agent role, is reinitializing itself and that its
    configuration may have been altered."
 ::= { snmpTraps 1 }

warmStart NOTIFICATION-TYPE
  STATUS current
  DESCRIPTION
    "A warmStart trap signifies that the SNMPv2 entity, acting
    in an agent role, is reinitializing itself such that its
    configuration is unaltered."
 ::= { snmpTraps 2 }

-- Note the linkDown NOTIFICATION-TYPE ::= { snmpTraps 3 }
-- and the linkUp NOTIFICATION-TYPE ::= { snmpTraps 4 }
-- are defined in RFC 1573

authenticationFailure NOTIFICATION-TYPE
  STATUS current
  DESCRIPTION
    "An authenticationFailure trap signifies that the SNMPv2
    entity, acting in an agent role, has received a protocol
    message that is not properly authenticated.  While all
    implementations of the SNMPv2 must be capable of generating
    this trap, the snmpEnableAuthenTraps object indicates
    whether this trap will be generated."
 ::= { snmpTraps 5 }

-- Note the egpNeighborLoss NOTIFICATION-TYPE ::= { snmpTraps 6 }
-- is defined in RFC 1213
```

```
-- the set group
--
-- a collection of objects which allow several cooperating
-- SNMPv2 entities, all acting in a manager role, to
-- coordinate their use of the SNMPv2 set operation.

snmpSet          OBJECT IDENTIFIER ::= { snmpMIBObjects 6 }

snmpSetSerialNo OBJECT-TYPE
    SYNTAX      TestAndIncr
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "An advisory lock used to allow several cooperating SNMPv2
        entities, all acting in a manager role, to coordinate their
        use of the SNMPv2 set operation.

        This object is used for coarse-grain coordination. To
        achieve fine-grain coordination, one or more similar objects
        might be defined within each MIB group, as appropriate."
    ::= { snmpSet 1 }

-- conformance information

snmpMIBConformance
    OBJECT IDENTIFIER ::= { snmpMIB 2 }

snmpMIBCompliances
    OBJECT IDENTIFIER ::= { snmpMIBConformance 1 }
snmpMIBGroups    OBJECT IDENTIFIER ::= { snmpMIBConformance 2 }

-- compliance statements

--      ::= { snmpMIBCompliances 1 }      this OID is obsolete

snmpBasicCompliance MODULE-COMPLIANCE
    STATUS      current
    DESCRIPTION
        "The compliance statement for SNMPv2 entities which
        implement the SNMPv2 MIB."
    MODULE     -- this module
        MANDATORY-GROUPS { snmpGroup, snmpSetGroup, systemGroup,
                           snmpBasicNotificationsGroup }

    GROUP      snmpCommunityGroup
```

```
DESCRIPTION
    "This group is mandatory for SNMPv2 entities which
    support community-based authentication."

 ::= { snmpMIBCompliances 2 }

-- units of conformance

-- ::= { snmpMIBGroups 1 }           this OID is obsolete
-- ::= { snmpMIBGroups 2 }           this OID is obsolete
-- ::= { snmpMIBGroups 3 }           this OID is obsolete
-- ::= { snmpMIBGroups 4 }           this OID is obsolete

snmpGroup OBJECT-GROUP
    OBJECTS { snmpInPkts,
              snmpInBadVersions,
              snmpInASNParseErrs,
              snmpSilentDrops,
              snmpProxyDrops,
              snmpEnableAuthenTraps }
    STATUS current
    DESCRIPTION
        "A collection of objects providing basic instrumentation and
        control of an SNMPv2 entity."
    ::= { snmpMIBGroups 8 }

snmpCommunityGroup OBJECT-GROUP
    OBJECTS { snmpInBadCommunityNames,
              snmpInBadCommunityUses }
    STATUS current
    DESCRIPTION
        "A collection of objects providing basic instrumentation of
        a SNMPv2 entity which supports community-based
        authentication."
    ::= { snmpMIBGroups 9 }

snmpSetGroup OBJECT-GROUP
    OBJECTS { snmpSetSerialNo }
    STATUS current
    DESCRIPTION
        "A collection of objects which allow several cooperating
        SNMPv2 entities, all acting in a manager role, to coordinate
        their use of the SNMPv2 set operation."
    ::= { snmpMIBGroups 5 }

systemGroup OBJECT-GROUP
    OBJECTS { sysDescr, sysObjectID, sysUpTime,
```

```
        sysContact, sysName, sysLocation,
        sysServices,
        sysORLastChange, sysORID,
        sysORUpTime, sysORDescr }
STATUS    current
DESCRIPTION
    "The system group defines objects which are common to all
    managed systems."
 ::= { snmpMIBGroups 6 }

snmpBasicNotificationsGroup NOTIFICATION-GROUP
NOTIFICATIONS { coldStart, authenticationFailure }
STATUS        current
DESCRIPTION
    "The two notifications which an SNMPv2 entity is required to
    implement."
 ::= { snmpMIBGroups 7 }

-- definitions in RFC 1213 made obsolete by the inclusion of a
-- subset of the snmp group in this MIB

snmpOutPkts OBJECT-TYPE
SYNTAX        Counter32
MAX-ACCESS    read-only
STATUS        obsolete
DESCRIPTION
    "The total number of SNMP Messages which were
    passed from the SNMP protocol entity to the
    transport service."
 ::= { snmp 2 }

-- { snmp 7 } is not used

snmpInTooBig OBJECT-TYPE
SYNTAX        Counter32
MAX-ACCESS    read-only
STATUS        obsolete
DESCRIPTION
    "The total number of SNMP PDUs which were
    delivered to the SNMP protocol entity and for
    which the value of the error-status field is
    'tooBig'."
 ::= { snmp 8 }

snmpInNoSuchNames OBJECT-TYPE
SYNTAX        Counter32
MAX-ACCESS    read-only
```

```
STATUS      obsolete
DESCRIPTION
    "The total number of SNMP PDUs which were
    delivered to the SNMP protocol entity and for
    which the value of the error-status field is
    'noSuchName'."
 ::= { snmp 9 }

snmpInBadValues OBJECT-TYPE
SYNTAX      Counter32
MAX-ACCESS  read-only
STATUS      obsolete
DESCRIPTION
    "The total number of SNMP PDUs which were
    delivered to the SNMP protocol entity and for
    which the value of the error-status field is
    'badValue'."
 ::= { snmp 10 }

snmpInReadOnly OBJECT-TYPE
SYNTAX      Counter32
MAX-ACCESS  read-only
STATUS      obsolete
DESCRIPTION
    "The total number valid SNMP PDUs which were
    delivered to the SNMP protocol entity and for
    which the value of the error-status field is
    'readOnly'. It should be noted that it is a
    protocol error to generate an SNMP PDU which
    contains the value 'readOnly' in the error-status
    field, as such this object is provided as a means
    of detecting incorrect implementations of the
    SNMP."
 ::= { snmp 11 }

snmpInGenErrs OBJECT-TYPE
SYNTAX      Counter32
MAX-ACCESS  read-only
STATUS      obsolete
DESCRIPTION
    "The total number of SNMP PDUs which were
    delivered to the SNMP protocol entity and for
    which the value of the error-status field is
    'genErr'."
 ::= { snmp 12 }

snmpInTotalReqVars OBJECT-TYPE
SYNTAX      Counter32
```

```
MAX-ACCESS    read-only
STATUS        obsolete
DESCRIPTION
    "The total number of MIB objects which have been
    retrieved successfully by the SNMP protocol entity
    as the result of receiving valid SNMP Get-Request
    and Get-Next PDUs."
 ::= { snmp 13 }

snmpInTotalSetVars OBJECT-TYPE
SYNTAX        Counter32
MAX-ACCESS    read-only
STATUS        obsolete
DESCRIPTION
    "The total number of MIB objects which have been
    altered successfully by the SNMP protocol entity
    as the result of receiving valid SNMP Set-Request
    PDUs."
 ::= { snmp 14 }

snmpInGetRequests OBJECT-TYPE
SYNTAX        Counter32
MAX-ACCESS    read-only
STATUS        obsolete
DESCRIPTION
    "The total number of SNMP Get-Request PDUs which
    have been accepted and processed by the SNMP
    protocol entity."
 ::= { snmp 15 }

snmpInGetNexts OBJECT-TYPE
SYNTAX        Counter32
MAX-ACCESS    read-only
STATUS        obsolete
DESCRIPTION
    "The total number of SNMP Get-Next PDUs which have
    been accepted and processed by the SNMP protocol
    entity."
 ::= { snmp 16 }

snmpInSetRequests OBJECT-TYPE
SYNTAX        Counter32
MAX-ACCESS    read-only
STATUS        obsolete
DESCRIPTION
    "The total number of SNMP Set-Request PDUs which
    have been accepted and processed by the SNMP
    protocol entity."
```

```
::= { snmp 17 }
```

```
snmpInGetResponses OBJECT-TYPE
```

```
SYNTAX Counter32
```

```
MAX-ACCESS read-only
```

```
STATUS obsolete
```

```
DESCRIPTION
```

```
"The total number of SNMP Get-Response PDUs which  
have been accepted and processed by the SNMP  
protocol entity."
```

```
::= { snmp 18 }
```

```
snmpInTraps OBJECT-TYPE
```

```
SYNTAX Counter32
```

```
MAX-ACCESS read-only
```

```
STATUS obsolete
```

```
DESCRIPTION
```

```
"The total number of SNMP Trap PDUs which have  
been accepted and processed by the SNMP protocol  
entity."
```

```
::= { snmp 19 }
```

```
snmpOutTooBigs OBJECT-TYPE
```

```
SYNTAX Counter32
```

```
MAX-ACCESS read-only
```

```
STATUS obsolete
```

```
DESCRIPTION
```

```
"The total number of SNMP PDUs which were  
generated by the SNMP protocol entity and for  
which the value of the error-status field is  
'tooBig.'"
```

```
::= { snmp 20 }
```

```
snmpOutNoSuchNames OBJECT-TYPE
```

```
SYNTAX Counter32
```

```
MAX-ACCESS read-only
```

```
STATUS obsolete
```

```
DESCRIPTION
```

```
"The total number of SNMP PDUs which were  
generated by the SNMP protocol entity and for  
which the value of the error-status is  
'noSuchName'."
```

```
::= { snmp 21 }
```

```
snmpOutBadValues OBJECT-TYPE
```

```
SYNTAX Counter32
```

```
MAX-ACCESS read-only
```

```
STATUS obsolete
```



```
DESCRIPTION
    "The total number of SNMP PDUs which were
    generated by the SNMP protocol entity and for
    which the value of the error-status field is
    'badValue'."
 ::= { snmp 22 }

-- { snmp 23 } is not used

snmpOutGenErrs OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      obsolete
    DESCRIPTION
        "The total number of SNMP PDUs which were
        generated by the SNMP protocol entity and for
        which the value of the error-status field is
        'genErr'."
 ::= { snmp 24 }

snmpOutGetRequests OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      obsolete
    DESCRIPTION
        "The total number of SNMP Get-Request PDUs which
        have been generated by the SNMP protocol entity."
 ::= { snmp 25 }

snmpOutGetNexts OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      obsolete
    DESCRIPTION
        "The total number of SNMP Get-Next PDUs which have
        been generated by the SNMP protocol entity."
 ::= { snmp 26 }

snmpOutSetRequests OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      obsolete
    DESCRIPTION
        "The total number of SNMP Set-Request PDUs which
        have been generated by the SNMP protocol entity."
 ::= { snmp 27 }
```

```
snmpOutGetResponses OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      obsolete
    DESCRIPTION
        "The total number of SNMP Get-Response PDUs which
         have been generated by the SNMP protocol entity."
    ::= { snmp 28 }

snmpOutTraps OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      obsolete
    DESCRIPTION
        "The total number of SNMP Trap PDUs which have
         been generated by the SNMP protocol entity."
    ::= { snmp 29 }

snmpObsoleteGroup OBJECT-GROUP
    OBJECTS { snmpOutPkts, snmpInTooBigs, snmpInNoSuchNames,
              snmpInBadValues, snmpInReadOnlys, snmpInGenErrs,
              snmpInTotalReqVars, snmpInTotalSetVars,
              snmpInGetRequests, snmpInGetNexts, snmpInSetRequests,
              snmpInGetResponses, snmpInTraps, snmpOutTooBigs,
              snmpOutNoSuchNames, snmpOutBadValues, snmpOutGenErrs,
              snmpOutGetRequests, snmpOutGetNexts, snmpOutSetRequests,
              snmpOutGetResponses, snmpOutTraps }
    STATUS      obsolete
    DESCRIPTION
        "A collection of objects from RFC 1213 made obsolete by this
         MIB."
    ::= { snmpMIBGroups 10 }

END
```

3. Security Considerations

Security issues are not discussed in this memo.

4. Editor's Address

Keith McCloghrie
Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
US

Phone: +1 408 526 5260
EMail: kzm@cisco.com

5. Acknowledgements

This document is the result of significant work by the four major contributors:

Jeffrey D. Case (SNMP Research, case@snmp.com)
Keith McCloghrie (Cisco Systems, kzm@cisco.com)
Marshall T. Rose (Dover Beach Consulting, mrose@dbc.mtview.ca.us)
Steven Waldbusser (International Network Services, stevew@uni.ins.com)

In addition, the contributions of the SNMPv2 Working Group are acknowledged. In particular, a special thanks is extended for the contributions of:

Alexander I. Alten (Novell)
Dave Arneson (Cabletron)
Uri Blumenthal (IBM)
Doug Book (Chipcom)
Kim Curran (Bell-Northern Research)
Jim Galvin (Trusted Information Systems)
Maria Greene (Ascom Timeplex)
Iain Hanson (Digital)
Dave Harrington (Cabletron)
Nguyen Hien (IBM)
Jeff Johnson (Cisco Systems)
Michael Kornegay (Object Quest)
Deirdre Kostick (AT&T Bell Labs)
David Levi (SNMP Research)
Daniel Mahoney (Cabletron)
Bob Natale (ACE*COMM)
Brian O'Keefe (Hewlett Packard)
Andrew Pearson (SNMP Research)
Dave Perkins (Peer Networks)
Randy Presuhn (Peer Networks)
Aleksy Romanov (Quality Quorum)
Shawn Routhier (Epilogue)
Jon Saperia (BGS Systems)

Bob Stewart (Cisco Systems, bstewart@cisco.com), chair
Kaj Tesink (Bellcore)
Glenn Waters (Bell-Northern Research)
Bert Wijnen (IBM)

6. References

- [1] Information processing systems - Open Systems Interconnection - Specification of Abstract Syntax Notation One (ASN.1), International Organization for Standardization. International Standard 8824, (December, 1987).
- [2] SNMPv2 Working Group, Case, J., McCloghrie, K., Rose, M., and S. Waldbusser, "Structure of Management Information for Version 2 of the Simple Network Management Protocol (SNMPv2)", RFC 1902, January 1996.
- [3] SNMPv2 Working Group, Case, J., McCloghrie, K., Rose, M., and S. Waldbusser, "Protocol Operations for Version 2 of the Simple Network Management Protocol (SNMPv2)", RFC 1905, January 1996.
- [4] J.D. Case, C. Partridge, Case Diagrams: A First Step to Diagrammed Management Information Bases. Computer Communications Review, Volume 19, Number 1, (January, 1989).