

Package ‘RKEEL’

September 14, 2023

Type Package

Title Using 'KEEL' in R Code

Version 1.3.4

Depends R (>= 3.4.0)

Date 2023-09-07

Author Jose M. Moyano [aut, cre],
Luciano Sanchez [aut],
Oliver Sanchez [ctb],
Jesus Alcala-Fernandez [ctb]

Maintainer Jose M. Moyano <jmoyano1@us.es>

Description

'KEEL' is a popular 'Java' software for a large number of different knowledge data discovery tasks. This package takes the advantages of 'KEEL' and R, allowing to use 'KEEL' algorithms in simple R code.

The implemented R code layer between R and 'KEEL' makes easy both using 'KEEL' algorithms in R as implementing new algorithms for 'RKEEL' in a very simple way.

It includes more than 100 algorithms for classification, regression, preprocess, association rules and imbalance learning, which allows a more complete experimentation process.

For more information about 'KEEL', see <<http://www.keel.es/>>.

SystemRequirements Java (>= 8)

License GPL

Imports R6, XML, doParallel, foreach, gdata, RKEELdata (>= 1.0.5),
pmml, arules, Matrix, rJava, openssl, downloader

NeedsCompilation no

Repository CRAN

Date/Publication 2023-09-14 18:50:08 UTC

R topics documented:

ABB_IEP_FS	5
AdaBoostNC_C	6

AdaBoost_I	7
Alatasetal_A	8
Alcalaetal_A	12
AllKNN_TSS	15
AllPossible_MV	16
ANR_F	17
Apriori_A	18
ART_C	21
AssociationRulesAlgorithm	22
AssociativeClassificationAlgorithm	22
Bayesian_D	23
BNGE_C	23
Bojarczuk_GP_C	24
BSE_C	25
C45Binarization_C	26
C45Rules_C	27
C45_C	28
CamNN_C	29
CART_C	29
CART_R	30
CBA_C	31
CenterNN_C	32
CFAR_C	32
CFKNN_C	33
CHC_C	34
ClassificationAlgorithm	35
ClassificationResults	35
CleanAttributes_TR	36
ClusterAnalysis_D	36
CMAR_C	37
CNN_C	38
CPAR_C	39
CPW_C	40
CW_C	41
C_SVM_C	42
DecimalScaling_TR	43
DecrRBFN_C	43
Deeps_C	44
downloadFromMirror	45
DSM_C	46
DT_GA_C	47
EARMGA_A	48
Eclat_A	51
EPSILON_SVR_R	55
Falco_GP_C	56
FCRA_C	57
FPgrowth_A	58
FRNN_C	61

FRSBM_R	62
FURIA_C	63
FuzzyApriori_A	64
FuzzyFARCHD_C	67
FuzzyKNN_C	68
FuzzyNPC_C	69
GANN_C	70
GAR_A	72
GENAR_A	76
GeneticFuzzyAprioriDC_A	79
GeneticFuzzyApriori_A	83
getAttributeLinesFromDataframes	87
getExePath	88
getJarList	88
getJarPath	89
GFS_AdaBoost_C	89
GFS_GP_R	90
GFS_GSP_R	91
GFS_LogitBoost_C	93
GFS_RB_MF_R	94
hasContinuousData	95
hasMissingValues	95
ID3_C	96
ID3_D	96
IF_KNN_C	97
Ignore_MV	98
ImbalancedClassificationAlgorithm	99
IncrRBFN_C	99
isMultiClass	100
IterativePartitioningFilter_F	100
JFKNN_C	101
KeelAlgorithm	102
Kernel_C	102
KMeans_MV	103
KNN_C	104
KNN_MV	104
KSNN_C	105
KStar_C	106
LDA_C	107
LinearLMS_C	108
LinearLMS_R	108
loadKeelDataset	109
Logistic_C	110
LVF_IEP_FS	110
M5Rules_R	111
M5_R	112
MinMax_TR	113
MLP_BP_C	114

MLP_BP_R	115
ModelCS_TSS	116
MODENAR_A	117
MOEA_Ghosh_A	121
MOPNAR_A	124
MostCommon_MV	128
NB_C	129
NICGAR_A	130
NM_C	133
NNEP_C	134
Nominal2Binary_TR	135
NU_SVM_C	136
NU_SVR_R	137
PART_C	138
PDFC_C	138
PFKNN_C	140
PNN_C	140
PolQuadraticLMS_C	141
PolQuadraticLMS_R	142
POP_TSS	143
PreprocessAlgorithm	144
PRISM_C	144
Proportional_D	145
PSO_ACO_C	146
PSRCG_TSS	147
PUBLIC_C	148
PW_C	149
QAR_CIP_NSGAII_A	150
QDA_C	153
RBFN_C	154
RBFN_R	155
read.keel	156
RegressionAlgorithm	156
RegressionResults	156
Relief_FS	157
Ripper_C	158
RISE_C	159
runCV	159
runParallel	160
runSequential	161
SaturationFilter_F	162
SFS_IEP_FS	163
SGA_C	163
Shrink_C	165
Slipper_C	165
SMO_C	166
SSGA_Integer_knn_FS	168
Tan_GP_C	169

Thrift_R 170
 UniformFrequency_D 171
 UniformWidth_D 172
 VWFuzzyKNN_C 173
 WM_R 173
 writeDatFromDataframe 174
 writeDatFromDataframes 175
 ZScore_TR 175

Index **177**

ABB_IEP_FS *ABB_IEP_FS KEEL Preprocess Algorithm*

Description

ABB_IEP_FS Preprocess Algorithm from KEEL.

Usage

ABB_IEP_FS(train, test, seed)

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::ABB_IEP_FS(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$preprocessed_test
```

AdaBoostNC_C

AdaBoostNC_C KEEL Classification Algorithm

Description

AdaBoostNC_C Classification Algorithm from KEEL.

Usage

```
AdaBoostNC_C(train, test, pruned, confidence, instancesPerLeaf,
             numClassifiers, algorithm, trainMethod, lambda, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
pruned	pruned. Default value = TRUE
confidence	confidence. Default value = 0.25
instancesPerLeaf	instancesPerLeaf. Default value = 2
numClassifiers	numClassifiers. Default value = 10
algorithm	algorithm. Default value = "ADABOOST.NC"
trainMethod	trainMethod. Default value = "NORESAMPLING"
lambda	lambda. Default value = 2
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::AdaBoostNC_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

Description

AdaBoost_I Imbalanced Classification Algorithm from KEEL.

Usage

```
AdaBoost_I(train, test, pruned, confidence, instancesPerLeaf,  
            numClassifiers, algorithm, trainMethod, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
pruned	pruned. Default value = TRUE
confidence	confidence. Default value = 0.25
instancesPerLeaf	instancesPerLeaf. Default value = 2
numClassifiers	numClassifiers. Default value = 10
algorithm	algorithm. Default value = "ADABOOST"
trainMethod	trainMethod. Default value = "NORESAMPLING"
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")  
data_test <- RKEEL::loadKeelDataset("iris_test")  
  
#Create algorithm  
algorithm <- RKEEL::AdaBoost_I(data_train, data_test)  
  
#Run algorithm  
algorithm$run()  
  
#See results  
algorithm$testPredictions
```

Alatasetal_A

Alatasetal_A KEEL Association Rules Algorithm

Description

Alatasetal_A Association Rules Algorithm from KEEL.

Usage

```
Alatasetal_A(dat, seed, NumberofEvaluations, InitialRandomChromosomes,
             rDividingPoints, TournamentSize, ProbabilityofCrossover,
             MinimumProbabilityofMutation, MaximumProbabilityofMutation,
             ImportanceofRulesSupport, ImportanceofRulesConfidence,
             ImportanceofNumberofInvolvedAttributes, ImportanceofIntervalsAmplitude,
             ImportanceofNumberofRecordsAlreadyCovered, AmplitudeFactor)
```

Arguments

dat	Dataset as a data.frame object
seed	seed. Default value = 1286082570
NumberofEvaluations	NumberofEvaluations. Default value = 50000
InitialRandomChromosomes	Initial Random Chromosomes. Default value = 12
rDividingPoints	r-Dividing Points. Default value = 3
TournamentSize	TournamentSize. Default value = 10
ProbabilityofCrossover	Probability of Crossover. Default value = 0.7
MinimumProbabilityofMutation	Minimum Probability of Mutation. Default value = 0.05
MaximumProbabilityofMutation	Maximum Probability of Mutation. Default value = 0.9
ImportanceofRulesSupport	Importance of Rules Support. Default value = 5
ImportanceofRulesConfidence	Importance of Rules Confidence. Default value = 20
ImportanceofNumberofInvolvedAttributes	Importance of Number of Involved Attributes. Default value = 0.05
ImportanceofIntervalsAmplitude	Importance of Intervals Amplitude. Default value = 0.02
ImportanceofNumberofRecordsAlreadyCovered	Importance of Number of Records Already Covered. Default value = 0.01
AmplitudeFactor	Amplitude Factor. Default value = 2.0

Details

`$run()` Run algorithm

`$showRules(numRules)` Show a number of rules. By default all rules.

`$getInterestMeasures()` Return a data.frame with all interest measures of set rules.

`$sortBy(interestMeasure)` Order set rules by interest measure.

`$writeCSV(fileName, sep)` Create CSV file with set rules. Default `fileName="rules"` `sep=","`

`$writePMML(fileName)` Create PMML file with set rules. Default `fileName="rules"`

`$addInterestMeasure(name, colName)` Add interest measures to set rules. Some interest measures supported:

"allConfidence" (Omiencinski, 2003)

"crossSupportRatio", cross-support ratio (Xiong et al., 2003)

"lift", interest factor (Brin et al. 1997)

"support", supp (Agrawal et al., 1996)

"addedValue", added Value, AV, Pavillon index, centered confidence (Tan et al., 2002)

"chiSquared", X^2 (Liu et al., 1999)

"certainty", certainty factor, CF, Loevinger (Berzal et al., 2002)

"collectiveStrength"

"confidence", conf (Agrawal et al., 1996)

"conviction" (Brin et al. 1997)

"cosine" (Tan et al., 2004)

"coverage", cover, LHS-support

"confirmedConfidence", descriptive confirmed confidence (Kodratoff, 1999)

"casualConfidence", casual confidence (Kodratoff, 1999)

"casualSupport", casual support (Kodratoff, 1999)

"counterexample", example and counterexample rate

"descriptiveConfirm", descriptive-confirm (Kodratoff, 1999)

"doc", difference of confidence (Hofmann and Wilhelm, 2001)

"fishersExactTest", Fisher's exact test (Hahsler and Hornik, 2007)

"gini", Gini index (Tan et al., 2004)

"hyperLift" (Hahsler and Hornik, 2007)

"hyperConfidence" (Hahsler and Hornik, 2007)

"imbalance", imbalance ratio, IR (Wu, Chen and Han, 2010)

"implicationIndex", implication index (Gras, 1996)

"improvement" (Bayardo et al., 2000)

"jaccard", Jaccard coefficient (Tan and Kumar, 2000)

"jMeasure", J-measure, J (Smyth and Goodman, 1991)

"kappa" (Tan and Kumar, 2000)

"kloggen", Kloggen (Tan and Kumar, 2000)

"kulczynski" (Wu, Chen and Han, 2007; Kulczynski, 1927)

"lambda", Goodman-Kruskal lambda, predictive association (Tan and Kumar, 2000)

"laplace", L (Tan and Kumar 2000)

"leastContradiction", least contradiction (Aze and Kodratoff, 2004)

"lerman", Lerman similarity (Lerman, 1981)

"leverage", PS (Piatetsky-Shapiro 1991)

"mutualInformation", uncertainty, M (Tan et al., 2002)

"oddsRatio", odds ratio alpha (Tan et al., 2004)

"phi", correlation coefficient phi (Tan et al. 2004)

"ralambrodriainy", Ralambrodriainy Measure (Ralambrodriainy, 1991)

"RLD", relative linkage disequilibrium (Kenett and Salini, 2008)

"sebag", Sebag measure (Sebag and Schoenauer, 1988)

"support", supp (Agrawal et al., 1996)

"varyingLiaison", varying rates liaison (Bernard and Charron, 1996)

"yuleQ", Yule's Q (Tan and Kumar, 2000)

"yuleY", Yule's Y (Tan and Kumar, 2000)

For more information see ?arules::interestMeasure

Value

A arules class with the Association Rules for both dat dataset.

Examples

```
#Load KEEL dataset
dat<-RKEEL::loadKeelDataset("car")

#Create algorithm
algorithm <- RKEEL::Alatasetal_A(dat)

#Run algorithm
algorithm$run()

#Rules in format arules
algorithm$rules

#Show a number of rules
algorithm$showRules(2)

#Return a data.frame with all interest measures of set rules
algorithm$getInterestMeasures()

#Add interest measure YuleY to set rules
algorithm$addInterestMeasure("YuleY", "yulesY")

#Sort by interest measure lift
algorithm$sortBy("lift")

#Save rules in CSV file
algorithm$writeCSV(paste0(tempdir(), "/myrules"))
```

Alcalaetal_A

Alcalaetal_A KEEL Association Rules Algorithm

Description

Alcalaetal_A Association Rules Algorithm from KEEL.

Usage

```
Alcalaetal_A(dat, seed, NumberofEvaluations, PopulationSize, NumberofBitsperGene,
  DecreasingFactorofLthresholdNOTUSED, FactorforParentCentricBLXCrossover,
  NumberofFuzzyRegionsforNumericAttributes, UseMaxOperatorfor1FrequentItemsets,
  MinimumSupport, MinimumConfidence)
```

Arguments

dat	Dataset as a data.frame object
seed	seed. Default value = 1286082570
NumberofEvaluations	Number of Evaluations. Default value = 10000
PopulationSize	Population Size. Default value = 50
NumberofBitsperGene	Number of Bits per Gene. Default value = 30
DecreasingFactorofLthresholdNOTUSED	Decreasing Factor of Lthreshold NOT USED. Default value = 0.1
FactorforParentCentricBLXCrossover	Factor for Parent Centric BLXCrossover. Default value = 1.0
NumberofFuzzyRegionsforNumericAttributes	Number of Fuzzy Regions for Numeric Attributes. Default value = 3
UseMaxOperatorfor1FrequentItemsets	Use Max Operator for 1 Frequent Itemsets. Default value = "false"
MinimumSupport	Minimum Support. Default value = 0.1
MinimumConfidence	Minimum Confidence. Default value = 0.8

Details

`$run()` Run algorithm

`$showRules(numRules)` Show a number of rules. By default all rules.

`$getInterestMeasures()` Return a data.frame with all interest measures of set rules.

`$sortBy(interestMeasure)` Order set rules by interest measure.

`$writeCSV(fileName, sep)` Create CSV file with set rules. Default `fileName="rules"` `sep=", "`

`$writePMML(fileName)` Create PMML file with set rules. Default `fileName="rules"`

`$addInterestMeasure(name, colName)` Add interest measures to set rules. Some interest measures supported:

"allConfidence" (Omiencinski, 2003)

"crossSupportRatio", cross-support ratio (Xiong et al., 2003)

"lift", interest factor (Brin et al. 1997)

"support", supp (Agrawal et al., 1996)

"addedValue", added Value, AV, Pavillon index, centered confidence (Tan et al., 2002)

"chiSquared", X^2 (Liu et al., 1999)

"certainty", certainty factor, CF, Loevinger (Berzal et al., 2002)

"collectiveStrength"

"confidence", conf (Agrawal et al., 1996)

"conviction" (Brin et al. 1997)

"cosine" (Tan et al., 2004)

"coverage", cover, LHS-support

"confirmedConfidence", descriptive confirmed confidence (Kodratoff, 1999)

"casualConfidence", casual confidence (Kodratoff, 1999)

"casualSupport", casual support (Kodratoff, 1999)

"counterexample", example and counterexample rate

"descriptiveConfirm", descriptive-confirm (Kodratoff, 1999)

"doc", difference of confidence (Hofmann and Wilhelm, 2001)

"fishersExactTest", Fisher's exact test (Hahsler and Hornik, 2007)

"gini", Gini index (Tan et al., 2004)

"hyperLift" (Hahsler and Hornik, 2007)

"hyperConfidence" (Hahsler and Hornik, 2007)

"imbalance", imbalance ratio, IR (Wu, Chen and Han, 2010)

"implicationIndex", implication index (Gras, 1996)

"improvement" (Bayardo et al., 2000)

"jaccard", Jaccard coefficient (Tan and Kumar, 2000)

"jMeasure", J-measure, J (Smyth and Goodman, 1991)

"kappa" (Tan and Kumar, 2000)

"kloggen", Kloggen (Tan and Kumar, 2000)

"kulczynski" (Wu, Chen and Han, 2007; Kulczynski, 1927)

"lambda", Goodman-Kruskal lambda, predictive association (Tan and Kumar, 2000)

"laplace", L (Tan and Kumar 2000)

"leastContradiction", least contradiction (Aze and Kodratoff, 2004)

"lerman", Lerman similarity (Lerman, 1981)

"leverage", PS (Piatetsky-Shapiro 1991)

"mutualInformation", uncertainty, M (Tan et al., 2002)

"oddsRatio", odds ratio alpha (Tan et al., 2004)

"phi", correlation coefficient phi (Tan et al. 2004)

"ralambrodriainy", Ralambrodriainy Measure (Ralambrodriainy, 1991)

"RLD", relative linkage disequilibrium (Kenett and Salini, 2008)

"sebag", Sebag measure (Sebag and Schoenauer, 1988)

"support", supp (Agrawal et al., 1996)

"varyingLiaison", varying rates liaison (Bernard and Charron, 1996)

"yuleQ", Yule's Q (Tan and Kumar, 2000)

"yuleY", Yule's Y (Tan and Kumar, 2000)

For more information see ?arules::interestMeasure

Value

A arules class with the Association Rules for both dat dataset.

Examples

```
#Load KEEL dataset
dat<-RKEEL::loadKeelDataset("car")

#Create algorithm
algorithm <- RKEEL::Alcalaetal_A(dat)

#Run algorithm
algorithm$run()

#Rules in format arules
algorithm$rules

#Show a number of rules
algorithm$showRules(2)

#Return a data.frame with all interest measures of set rules
algorithm$getInterestMeasures()

#Add interest measure YuleY to set rules
algorithm$addInterestMeasure("YuleY", "yulesY")

#Sort by interest measure lift
algorithm$sortBy("lift")

#Save rules in CSV file
algorithm$writeCSV(paste0(tempdir(), "/myrules"))
```

AllKNN_TSS

AllKNN_TSS KEEL Preprocess Algorithm

Description

AllKNN_TSS Preprocess Algorithm from KEEL.

Usage

```
AllKNN_TSS(train, test, k, distance)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
k	k. Default value = 3
distance	distance. Default value = "Euclidean"

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::AllKNN_TSS(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$preprocessed_test
```

AllPosible_MV

AllPosible_MV KEEL Preprocess Algorithm

Description

AllPosible_MV Preprocess Algorithm from KEEL.

Usage

```
AllPosible_MV(train, test)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::AllPosible_MV(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$preprocessed_test
```

ANR_F

ANR_F KEEL Preprocess Algorithm

Description

ANR_F Preprocess Algorithm from KEEL.

Usage

```
ANR_F(train, test, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("zoo")
data_test <- RKEEL::loadKeelDataset("zoo")

#Create algorithm
algorithm <- RKEEL::ANR_F(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$preprocessed_test
```

 Apriori_A

Apriori_A KEEL Association Rules Algorithm

Description

Apriori_A Association Rules Algorithm from KEEL.

Usage

```
Apriori_A(dat, NumberofPartitionsforNumericAttributes, MinimumSupport,
          MinimumConfidence)
```

Arguments

dat	Dataset as a data.frame object
NumberofPartitionsforNumericAttributes	Number of Partitions for Numeric Attributes. Default value = 4
MinimumSupport	Minimum Support. Default value = 0.1
MinimumConfidence	Minimum Confidence. Default value = 0.8

Details

`$run()` Run algorithm

`$showRules(numRules)` Show a number of rules. By default all rules.

`$getInterestMeasures()` Return a data.frame with all interest measures of set rules.

`$sortBy(interestMeasure)` Order set rules by interest measure.

`$writeCSV(fileName, sep)` Create CSV file with set rules. Default `fileName="rules"` `sep=","`

`$writePMML(fileName)` Create PMML file with set rules. Default `fileName="rules"`

`$addInterestMeasure(name, colName)` Add interest measures to set rules. Some interest measures supported:

"allConfidence" (Omiencinski, 2003)

"crossSupportRatio", cross-support ratio (Xiong et al., 2003)

"lift", interest factor (Brin et al. 1997)

"support", supp (Agrawal et al., 1996)

"addedValue", added Value, AV, Pavillon index, centered confidence (Tan et al., 2002)

"chiSquared", X^2 (Liu et al., 1999)

"certainty", certainty factor, CF, Loevinger (Berzal et al., 2002)

"collectiveStrength"

"confidence", conf (Agrawal et al., 1996)

"conviction" (Brin et al. 1997)

"cosine" (Tan et al., 2004)

"coverage", cover, LHS-support

"confirmedConfidence", descriptive confirmed confidence (Kodratoff, 1999)

"casualConfidence", casual confidence (Kodratoff, 1999)

"casualSupport", casual support (Kodratoff, 1999)

"counterexample", example and counterexample rate

"descriptiveConfirm", descriptive-confirm (Kodratoff, 1999)

"doc", difference of confidence (Hofmann and Wilhelm, 2001)

"fishersExactTest", Fisher's exact test (Hahsler and Hornik, 2007)

"gini", Gini index (Tan et al., 2004)

"hyperLift" (Hahsler and Hornik, 2007)

"hyperConfidence" (Hahsler and Hornik, 2007)

"imbalance", imbalance ratio, IR (Wu, Chen and Han, 2010)

"implicationIndex", implication index (Gras, 1996)

"improvement" (Bayardo et al., 2000)

"jaccard", Jaccard coefficient (Tan and Kumar, 2000)

"jMeasure", J-measure, J (Smyth and Goodman, 1991)

"kappa" (Tan and Kumar, 2000)

"klosgen", Klosgen (Tan and Kumar, 2000)

"kulczynski" (Wu, Chen and Han, 2007; Kulczynski, 1927)

"lambda", Goodman-Kruskal lambda, predictive association (Tan and Kumar, 2000)

"laplace", L (Tan and Kumar 2000)

"leastContradiction", least contradiction (Aze and Kodratoff, 2004)

"lerman", Lerman similarity (Lerman, 1981)

"leverage", PS (Piatetsky-Shapiro 1991)

"mutualInformation", uncertainty, M (Tan et al., 2002)

"oddsRatio", odds ratio alpha (Tan et al., 2004)

"phi", correlation coefficient phi (Tan et al. 2004)

"ralambrodriainy", Ralambrodriainy Measure (Ralambrodriainy, 1991)

"RLD", relative linkage disequilibrium (Kenett and Salini, 2008)

"sebag", Sebag measure (Sebag and Schoenauer, 1988)

"support", supp (Agrawal et al., 1996)

"varyingLiaison", varying rates liaison (Bernard and Charron, 1996)

"yuleQ", Yule's Q (Tan and Kumar, 2000)

"yuleY", Yule's Y (Tan and Kumar, 2000)

For more information see ?arules::interestMeasure

Value

A arules class with the Association Rules for both dat dataset.

Examples

```
#Load KEEL dataset
dat<-RKEEL::loadKeelDataset("car")

#Create algorithm
```

```
algorithm <- RKEEL::Apriori_A(dat)

#Run algorithm
algorithm$run()

#Rules in format arules
algorithm$rules

#Show a number of rules
algorithm$showRules(2)

#Return a data.frame with all interest measures of set rules
algorithm$getInterestMeasures()

#Add interest measure YuleY to set rules
algorithm$addInterestMeasure("YuleY", "yulesY")

#Sort by interest measure lift
algorithm$sortBy("lift")

#Save rules in CSV file
algorithm$writeCSV(paste0(tempdir(), "/myrules"))
```

ART_C

ART_C KEEL Classification Algorithm

Description

ART_C Classification Algorithm from KEEL.

Usage

```
ART_C(train, test)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
```

```

algorithm <- RKEEL::ART_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions

```

AssociationRulesAlgorithm

Association Rules Algorithm

Description

Class inheriting of KeelAlgorithm, to common methods for all KEEL Association Rules Algorithms. The specific association rules algorithms must inherit of this class.

The run() method receives three parameters. The folderPath parameter indicates where to place the folder with the experiments if wanted. If it is not indicated, the folder is placed in a temporary random directory and then removed. If indicated, the experiment folder is not removed. The expUniqueName parameter indicates the name of the experiment folder. If not indicated, it is a random name. If indicated, ensure that the name is unique in the previously indicated folder. The javaOptions parameter indicates, if wanted, extra parameters to the java command line, as for example the maximum memory allowed by java.

AssociativeClassificationAlgorithm

Associative Classification Algorithm

Description

Class inheriting of ClassificationAlgorithm, to common methods for Associative Classification Algorithms.

The run() method receives three parameters. The folderPath parameter indicates where to place the folder with the experiments if wanted. If it is not indicated, the folder is placed in a temporary random directory and then removed. If indicated, the experiment folder is not removed. The expUniqueName parameter indicates the name of the experiment folder. If not indicated, it is a random name. If indicated, ensure that the name is unique in the previously indicated folder. The javaOptions parameter indicates, if wanted, extra parameters to the java command line, as for example the maximum memory allowed by java.

Bayesian_D

Bayesian_D KEEL Preprocess Algorithm

Description

Bayesian_D Preprocess Algorithm from KEEL.

Usage

```
Bayesian_D(train, test)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::Bayesian_D(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$preprocessed_test
```

BNGE_C

BNGE_C KEEL Classification Algorithm

Description

BNGE_C Classification Algorithm from KEEL.

Usage

```
BNGE_C(train, test, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::BNGE_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

Bojarczuk_GP_C

Bojarczuk_GP_C KEEL Classification Algorithm

Description

Bojarczuk_GP_C Classification Algorithm from KEEL.

Usage

```
Bojarczuk_GP_C(train, test, population_size, max_generations,
  max_deriv_size, rec_prob, copy_prob, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
population_size	population_size. Default value = 200
max_generations	max_generations. Default value = 200
max_deriv_size	max_deriv_size. Default value = 20
rec_prob	rec_prob. Default value = 0.8

copy_prob	copy_prob. Default value = 0.01
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```

data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::Bojarczuk_GP_C(data_train, data_test)
algorithm <- RKEEL::Bojarczuk_GP_C(data_train, data_test, population_size=5, max_generations=10)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions

```

BSE_C

BSE_C KEEL Classification Algorithm

Description

BSE_C Classification Algorithm from KEEL.

Usage

```
BSE_C(train, test, k, distance)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
k	k. Default value = 1
distance	distance. Default value = "Euclidean"

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```

data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::BSE_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions

```

C45Binarization_C

C45Binarization_C KEEL Classification Algorithm

Description

C45Binarization_C Classification Algorithm from KEEL.

Usage

```

C45Binarization_C(train, test, pruned, confidence, instancesPerLeaf,
  binarization, scoreFunction, bts)

```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
pruned	pruned. Default value = TRUE
confidence	confidence. Default value = 0.25
instancesPerLeaf	instancesPerLeaf. Default value = 2
binarization	binarization. Default value = "OVO"
scoreFunction	scoreFunction. Default value = "WEIGHTED"
bts	bts. Default value = 0.05

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```

data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::C45Binarization_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions

```

C45Rules_C

C45Rules_C KEEL Classification Algorithm

Description

C45Rules_C Classification Algorithm from KEEL.

Usage

```

C45Rules_C(train, test, confidence, itemsetsPerLeaf, threshold,
  seed)

```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
confidence	confidence. Default value = 0.25
itemsetsPerLeaf	itemsetsPerLeaf. Default value = 2
threshold	threshold. Default value = 10
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```

data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::C45Rules_C(data_train, data_test)

```

```
#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

C45_C

C45_C KEEL Classification Algorithm

Description

C45_C Classification Algorithm from KEEL.

Usage

```
C45_C(train, test, pruned, confidence, instancesPerLeaf)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
pruned	pruned. Default value = TRUE
confidence	confidence. Default value = 0.25
instancesPerLeaf	instancesPerLeaf. Default value = 2

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::C45_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

CamNN_C

CamNN_C KEEL Classification Algorithm

Description

CamNN_C Classification Algorithm from KEEL.

Usage

```
CamNN_C(train, test, k)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
k	k. Default value = 1

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::CamNN_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

CART_C

CART_C KEEL Classification Algorithm

Description

CART_C Classification Algorithm from KEEL.

Usage

```
CART_C(train, test, maxDepth)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
maxDepth	k. Default value = 90

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::CART_C(data_train, data_test, maxDepth=3)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

CART_R

CART_R KEEL Regression Algorithm

Description

CART_R Regression Algorithm from KEEL.

Usage

```
CART_R(train, test, maxDepth)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
maxDepth	maxDepth. Default value = 90

Value

A data.frame with the actual and predicted values for both train and test datasets.

Examples

```

data_train <- RKEEL::loadKeelDataset("autoMPG6_train")
data_test <- RKEEL::loadKeelDataset("autoMPG6_test")

#Create algorithm
algorithm <- RKEEL::CART_R(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions

```

CBA_C

*CBA_C KEEL Associative Classification Algorithm***Description**

CBA_C Associative Classification Algorithm from KEEL.

Usage

```
CBA_C(train, test, min_support, min_confidence, pruning, maxCandidates)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
min_support	min_support. Default value = 0.01
min_confidence	min_confidence. Default value = 0.5
pruning	indicates wether pruning or not. Default value = TRUE
maxCandidates	maxCandidates; if 0, no limit. Default value = 80000

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```

data <- loadKeelDataset("breast")

#Create algorithm
algorithm <- RKEEL::CBA_C(data, data)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions

```

CenterNN_C

CenterNN_C KEEL Classification Algorithm

Description

CenterNN_C Classification Algorithm from KEEL.

Usage

```
CenterNN_C(train, test)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::CenterNN_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

CFAR_C

CFAR_C KEEL Classification Algorithm

Description

CFAR_C Classification Algorithm from KEEL.

Usage

```
CFAR_C(train, test, min_support, min_confidence, threshold,
        num_labels, seed)
```


Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
min_support	min_support. Default value = 0.1
min_confidence	min_confidence. Default value = 0.85
threshold	threshold. Default value = 0.15
num_labels	num_labels. Default value = 5
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::CFAR_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

CFKNN_C

CFKNN_C KEEL Classification Algorithm

Description

CFKNN_C Classification Algorithm from KEEL.

Usage

```
CFKNN_C(train, test, k, alpha, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
k	k. Default value = 3
alpha	alpha. Default value = 0.6
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::CFKNN_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

CHC_C

CHC_C KEEL Classification Algorithm

Description

CHC_C Classification Algorithm from KEEL.

Usage

```
CHC_C(train, test, pop_size, evaluations, alfa, restart_change,
       prob_restart, prob_diverge, k, distance, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
pop_size	pop_size. Default value = 50
evaluations	evaluations. Default value = 10000
alfa	alfa. Default value = 0.5
restart_change	restart_change. Default value = 0.35
prob_restart	prob_restart. Default value = 0.25
prob_diverge	prob_diverge. Default value = 0.05
k	k. Default value = 1
distance	distance. Default value = "Euclidean"
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::CHC_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

ClassificationAlgorithm

Classification Algorithm

Description

Class inheriting of KeelAlgorithm, to common methods for all KEEL Classification Algorithms. The specific classification algorithms must inherit of this class.

The run() method receives three parameters. The folderPath parameter indicates where to place the folder with the experiments if wanted. If it is not indicated, the folder is placed in a temporary random directory and then removed. If indicated, the experiment folder is not removed. The expUniqueName parameter indicates the name of the experiment folder. If not indicated, it is a random name. If indicated, ensure that the name is unique in the previously indicated folder. The javaOptions parameter indicates, if wanted, extra parameters to the java command line, as for example the maximum memory allowed by java.

ClassificationResults *Classification Results*

Description

Class to calculate and store some results for a ClassificationAlgorithm. It receives as parameter the prediction of a classification algorithm as a data.frame object.

CleanAttributes_TR *CleanAttributes_TR KEEL Preprocess Algorithm*

Description

CleanAttributes_TR Preprocess Algorithm from KEEL.

Usage

```
CleanAttributes_TR(train, test)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::CleanAttributes_TR(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$preprocessed_test
```

ClusterAnalysis_D *ClusterAnalysis_D KEEL Preprocess Algorithm*

Description

ClusterAnalysis_D Preprocess Algorithm from KEEL.

Usage

```
ClusterAnalysis_D(train, test)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::ClusterAnalysis_D(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$preprocessed_test
```

 CMAR_C

CMAR_C KEEL Associative Classification Algorithm

Description

CMAR_C Associative Classification Algorithm from KEEL.

Usage

```
CMAR_C(train, test, min_confidence, min_support, databaseCoverage)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
min_confidence	min_confidence. Default value = 0.5
min_support	min_support. Default value = 0.01
databaseCoverage	databaseCoverage. Default value = 4

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data <- loadKeelDataset("breast")

#Create algorithm
algorithm <- RKEEL::CMAR_C(data, data)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

CNN_C

CNN_C KEEL Classification Algorithm

Description

CNN_C Classification Algorithm from KEEL.

Usage

```
CNN_C(train, test, k, distance, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
k	k. Default value = 1
distance	distance. Default value = "Euclidean"
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::CNN_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

CPAR_C

CPAR_C KEEL Associative Classification Algorithm

Description

CPAR_C Associative Classification Algorithm from KEEL.

Usage

```
CPAR_C(train, test, delta, min_gain, alpha, rules_prediction)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
delta	delta. Default value = 0.05
min_gain	min_gain. Default value = 0.7
alpha	alpha. Default value = 0.66
rules_prediction	rules_prediction. Default value = 5

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data <- loadKeelDataset("breast")

#Create algorithm
algorithm <- RKEEL::CPAR_C(data, data)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

CPW_C

CPW_C KEEL Classification Algorithm

Description

CPW_C Classification Algorithm from KEEL.

Usage

```
CPW_C(train, test, beta, mu, ro, epsilon)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
beta	beta. Default value = 8.0
mu	mu. Default value = 0.001
ro	ro. Default value = 0.001
epsilon	epsilon. Default value = 0.001

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::CPW_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

CW_C

CW_C KEEL Classification Algorithm

Description

CW_C Classification Algorithm from KEEL.

Usage

```
CW_C(train, test, beta, mu, epsilon)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
beta	beta. Default value = 8.0
mu	mu. Default value = 0.001
epsilon	epsilon. Default value = 0.001

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::CW_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

C_SVM_C

*C_SVM_C KEEL Classification Algorithm***Description**

C_SVM_C Classification Algorithm from KEEL.

Usage

```
C_SVM_C(train, test, KernelType, C, eps, degree, gamma, coef0,
        nu, p, shrinking, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
KernelType	KernelType. Default value = "RBF"
C	C. Default value = 100.0
eps	eps. Default value = 0.001
degree	degree. Default value = 1
gamma	gamma. Default value = 0.01
coef0	coef0. Default value = 0.0
nu	nu. Default value = 0.1
p	p. Default value = 1.0
shrinking	shrinking. Default value = 1
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::C_SVM_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

DecimalScaling_TR *DecimalScaling_TR KEEL Preprocess Algorithm*

Description

DecimalScaling_TR Preprocess Algorithm from KEEL.

Usage

```
DecimalScaling_TR(train, test)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::DecimalScaling_TR(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$preprocessed_test
```

DecrRBFN_C *DecrRBFN_C KEEL Classification Algorithm*

Description

DecrRBFN_C Classification Algorithm from KEEL.

Usage

```
DecrRBFN_C(train, test, percent, num_neurons_ini, alfa, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
percent	percent. Default value = 0.1
num_neurons_ini	num_neurons_ini. Default value = 20
alfa	alfa. Default value = 0.3
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::DecrRBFN_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

Deeps_C

Deeps_C KEEL Classification Algorithm

Description

Deeps_C Classification Algorithm from KEEL.

Usage

```
Deeps_C(train, test, beta)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
beta	beta. Default value = 0.12

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::Deeps_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

downloadFromMirror	<i>Download file from a mirror</i>
--------------------	------------------------------------

Description

Downloads a file from a given mirror and checks its md5 sum. The file is stored in a given path

Usage

```
downloadFromMirror(mirror, file_path, md5_sum)
```

Arguments

mirror	URL from which to download the file.
file_path	Path or folder where the downloaded file will be stored.
md5_sum	md5 checksum string corresponding to the file to download. The method will check that the downloaded file checksum and the md5_sum parameter match.

Value

Returns 1 if the download was successful and -1 otherwise.

Examples

```
# Download RKEELjars file
dCode = RKEEL::downloadFromMirror("https://personal.us.es/jmoyano1/RKEELjars_1.1.zip",
  downloadedJarFile, md5_sum)

# Check if the download was successful
if(dCode<0){
```

```

    print('There was an error during the download.')
  }

```

DSM_C

DSM_C KEEL Classification Algorithm

Description

DSM_C Classification Algorithm from KEEL.

Usage

```
DSM_C(train, test, iterations, percentage, alpha_0, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
iterations	iterations. Default value = 100
percentage	percentage. Default value = 10
alpha_0	alpha_0. Default value = 0.1
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```

data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::DSM_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions

```

DT_GA_C *DT_GA_C KEEL Classification Algorithm*

Description

DT_GA_C Classification Algorithm from KEEL.

Usage

```
DT_GA_C(train, test, confidence, instancesPerLeaf,
         geneticAlgorithmApproach, threshold, numGenerations,
         popSize, crossoverProb, mutProb, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
confidence	confidence. Default value = 0.25
instancesPerLeaf	instancesPerLeaf. Default value = 2
geneticAlgorithmApproach	geneticAlgorithmApproach. Default value = "GA-LARGE-SN"
threshold	threshold. Default value = 10
numGenerations	numGenerations. Default value = 50
popSize	popSize. Default value = 200
crossoverProb	crossoverProb. Default value = 0.8
mutProb	mutProb. Default value = 0.01
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::DT_GA_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

EARMGA_A

*EARMGA_A KEEL Association Rules Algorithm***Description**

EARMGA_A Association Rules Algorithm from KEEL.

Usage

```
EARMGA_A(dat, seed, FixedLengthofAssociationRules, PopulationSize,
  TotalNumberOfEvaluations, DifferenceBoundaryNOTUSED, ProbabilityofSelection,
  ProbabilityofCrossover, ProbabilityofMutation,
  NumberofPartitionsforNumericAttributes)
```

Arguments

dat	Dataset as a data.frame object
seed	seed. Default value = 1286082570
FixedLengthofAssociationRules	Fixed Length of Association Rules. Default value = 2
PopulationSize	PopulationSize. Default value = 100
TotalNumberOfEvaluations	Total Number of Evaluations. Default value = 50000
DifferenceBoundaryNOTUSED	Difference Boundary NOT USED. Default value = 0.01
ProbabilityofSelection	Probability of Selection. Default value = 0.75
ProbabilityofCrossover	Probability of Crossover. Default value = 0.7
ProbabilityofMutation	Probability of Mutation. Default value = 0.1
NumberofPartitionsforNumericAttributes	Number of Partitions for Numeric Attributes. Default value = 4

Details

`$run()` Run algorithm

`$showRules(numRules)` Show a number of rules. By default all rules.

`$getInterestMeasures()` Return a data.frame with all interest measures of set rules.

`$sortBy(interestMeasure)` Order set rules by interest measure.

`$writeCSV(fileName, sep)` Create CSV file with set rules. Default `fileName="rules"` `sep=","`

`$writePMML(fileName)` Create PMML file with set rules. Default `fileName="rules"`

`$addInterestMeasure(name, colName)` Add interest measures to set rules. Some interest measures supported:

"allConfidence" (Omiencinski, 2003)

"crossSupportRatio", cross-support ratio (Xiong et al., 2003)

"lift", interest factor (Brin et al. 1997)

"support", supp (Agrawal et al., 1996)

"addedValue", added Value, AV, Pavillon index, centered confidence (Tan et al., 2002)

"chiSquared", X^2 (Liu et al., 1999)

"certainty", certainty factor, CF, Loevinger (Berzal et al., 2002)

"collectiveStrength"

"confidence", conf (Agrawal et al., 1996)

"conviction" (Brin et al. 1997)

"cosine" (Tan et al., 2004)

"coverage", cover, LHS-support

"confirmedConfidence", descriptive confirmed confidence (Kodratoff, 1999)

"casualConfidence", casual confidence (Kodratoff, 1999)

"casualSupport", casual support (Kodratoff, 1999)

"counterexample", example and counterexample rate

"descriptiveConfirm", descriptive-confirm (Kodratoff, 1999)

"doc", difference of confidence (Hofmann and Wilhelm, 2001)

"fishersExactTest", Fisher's exact test (Hahsler and Hornik, 2007)

"gini", Gini index (Tan et al., 2004)

"hyperLift" (Hahsler and Hornik, 2007)

"hyperConfidence" (Hahsler and Hornik, 2007)

"imbalance", imbalance ratio, IR (Wu, Chen and Han, 2010)

"implicationIndex", implication index (Gras, 1996)

"improvement" (Bayardo et al., 2000)

"jaccard", Jaccard coefficient (Tan and Kumar, 2000)

"jMeasure", J-measure, J (Smyth and Goodman, 1991)

"kappa" (Tan and Kumar, 2000)

"klogen", Klogen (Tan and Kumar, 2000)

"kulczynski" (Wu, Chen and Han, 2007; Kulczynski, 1927)

"lambda", Goodman-Kruskal lambda, predictive association (Tan and Kumar, 2000)

"laplace", L (Tan and Kumar 2000)

"leastContradiction", least contradiction (Aze and Kodratoff, 2004)

"lerman", Lerman similarity (Lerman, 1981)

"leverage", PS (Piatetsky-Shapiro 1991)

"mutualInformation", uncertainty, M (Tan et al., 2002)

"oddsRatio", odds ratio alpha (Tan et al., 2004)

"phi", correlation coefficient phi (Tan et al. 2004)

"ralambrodrainy", Ralambrodrainy Measure (Ralambrodrainy, 1991)

"RLD", relative linkage disequilibrium (Kenett and Salini, 2008)

"sebag", Sebag measure (Sebag and Schoenauer, 1988)

"support", supp (Agrawal et al., 1996)

"varyingLiaison", varying rates liaison (Bernard and Charron, 1996)

"yuleQ", Yule's Q (Tan and Kumar, 2000)

"yuleY", Yule's Y (Tan and Kumar, 2000)

For more information see `?arules::interestMeasure`

Value

A `arules` class with the Association Rules for both `dat` dataset.

Examples

```
#Load KEEL dataset
dat<-RKEEL::loadKeelDataset("car")

#Create algorithm
algorithm <- RKEEL::EARMGA_A(dat)

#Run algorithm
algorithm$run()

#Rules in format arules
algorithm$rules

#Show a number of rules
algorithm$showRules(2)

#Return a data.frame with all interest measures of set rules
algorithm$getInterestMeasures()

#Add interest measure YuleY to set rules
algorithm$addInterestMeasure("YuleY", "yulesY")

#Sort by interest measure lift
algorithm$sortBy("lift")

#Save rules in CSV file
algorithm$writeCSV(paste0(tempdir(), "/myrules"))
```

Eclat_A

Eclat_A KEEL Association Rules Algorithm

Description

Eclat_A Association Rules Algorithm from KEEL.

Usage

```
Eclat_A(dat, NumberofPartitionsforNumericAttributes, MinimumSupport,
        MinimumConfidence)
```

Arguments

`dat` Dataset as a `data.frame` object
`NumberOfPartitionsforNumericAttributes`
 Number of Partitions for Numeric Attributes. Default value = 4
`MinimumSupport` Minimum Support. Default value = 0.1
`MinimumConfidence`
 Minimum Confidence. Default value = 0.8

Details

`$run()` Run algorithm
`$showRules(numRules)` Show a number of rules. By default all rules.
`$getInterestMeasures()` Return a `data.frame` with all interest measures of set rules.
`$sortBy(interestMeasure)` Order set rules by interest measure.
`$writeCSV(fileName, sep)` Create CSV file with set rules. Default `fileName="rules"` `sep=","`
`$writePMML(fileName)` Create PMML file with set rules. Default `fileName="rules"`
`$addInterestMeasure(name, colName)` Add interest measures to set rules. Some interest measures supported:

- "allConfidence" (Omiencinski, 2003)
- "crossSupportRatio", cross-support ratio (Xiong et al., 2003)
- "lift", interest factor (Brin et al. 1997)
- "support", `supp` (Agrawal et al., 1996)
- "addedValue", added Value, AV, Pavillon index, centered confidence (Tan et al., 2002)
- "chiSquared", X^2 (Liu et al., 1999)
- "certainty", certainty factor, CF, Loevinger (Berzal et al., 2002)
- "collectiveStrength"
- "confidence", `conf` (Agrawal et al., 1996)
- "conviction" (Brin et al. 1997)
- "cosine" (Tan et al., 2004)

"coverage", cover, LHS-support

"confirmedConfidence", descriptive confirmed confidence (Kodratoff, 1999)

"casualConfidence", casual confidence (Kodratoff, 1999)

"casualSupport", casual support (Kodratoff, 1999)

"counterexample", example and counterexample rate

"descriptiveConfirm", descriptive-confirm (Kodratoff, 1999)

"doc", difference of confidence (Hofmann and Wilhelm, 2001)

"fishersExactTest", Fisher's exact test (Hahsler and Hornik, 2007)

"gini", Gini index (Tan et al., 2004)

"hyperLift" (Hahsler and Hornik, 2007)

"hyperConfidence" (Hahsler and Hornik, 2007)

"imbalance", imbalance ratio, IR (Wu, Chen and Han, 2010)

"implicationIndex", implication index (Gras, 1996)

"improvement" (Bayardo et al., 2000)

"jaccard", Jaccard coefficient (Tan and Kumar, 2000)

"jMeasure", J-measure, J (Smyth and Goodman, 1991)

"kappa" (Tan and Kumar, 2000)

"kloggen", Kloggen (Tan and Kumar, 2000)

"kulczynski" (Wu, Chen and Han, 2007; Kulczynski, 1927)

"lambda", Goodman-Kruskal lambda, predictive association (Tan and Kumar, 2000)

"laplace", L (Tan and Kumar 2000)

"leastContradiction", least contradiction (Aze and Kodratoff, 2004)

"lerman", Lerman similarity (Lerman, 1981)

"leverage", PS (Piatetsky-Shapiro 1991)

"mutualInformation", uncertainty, M (Tan et al., 2002)

"oddsRatio", odds ratio alpha (Tan et al., 2004)

"phi", correlation coefficient phi (Tan et al. 2004)

"ralambrodrainy", Ralambrodrainy Measure (Ralambrodrainy, 1991)

"RLD", relative linkage disequilibrium (Kenett and Salini, 2008)

"sebag", Sebag measure (Sebag and Schoenauer, 1988)

"support", supp (Agrawal et al., 1996)

"varyingLiaison", varying rates liaison (Bernard and Charron, 1996)

"yuleQ", Yule's Q (Tan and Kumar, 2000)

"yuleY", Yule's Y (Tan and Kumar, 2000)

For more information see ?arules::interestMeasure

Value

A arules class with the Association Rules for both dat dataset.

Examples

```
#Load KEEL dataset
dat<-RKEEL::loadKeelDataset("car")

#Create algorithm
algorithm <- RKEEL::Eclat_A(dat)

#Run algorithm
algorithm$run()

#Rules in format arules
algorithm$rules

#Show a number of rules
algorithm$showRules(2)

#Return a data.frame with all interest measures of set rules
algorithm$getInterestMeasures()

#Add interst measure YuleY to set rules
algorithm$addInterestMeasure("YuleY", "yulesY")
```

```
#Sort by interest measure lift
algorithm$sortBy("lift")

#Save rules in CSV file
algorithm$writeCSV(paste0(tempdir(), "/myrules"))
```

 EPSILON_SVR_R

EPSILON_SVR_R KEEL Regression Algorithm

Description

EPSILON_SVR_R Regression Algorithm from KEEL.

Usage

```
EPSILON_SVR_R(train, test, KernelType, C, eps, degree, gamma,
  coef0, nu, p, shrinking, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
KernelType	KernelType. Default value = "RBF"
C	C. Default value = 100.0
eps	eps. Default value = 0.001
degree	degree. Default value = 3
gamma	gamma. Default value = 0.01
coef0	coef0. Default value = 0.0
nu	nu. Default value = 0.5
p	p. Default value = 1.0
shrinking	shrinking. Default value = 0
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted values for both train and test datasets.

Examples

```

data_train <- RKEEL::loadKeelDataset("autoMPG6_train")
data_test <- RKEEL::loadKeelDataset("autoMPG6_test")

#Create algorithm
algorithm <- RKEEL::EPSILON_SVR_R(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions

```

Falco_GP_C

*Falco_GP_C KEEL Classification Algorithm***Description**

Falco_GP_C Classification Algorithm from KEEL.

Usage

```

Falco_GP_C(train, test, population_size, max_generations,
            max_deriv_size, rec_prob, mut_prob, copy_prob, alpha, seed)

```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
population_size	population_size. Default value = 200
max_generations	max_generations. Default value = 200
max_deriv_size	max_deriv_size. Default value = 20
rec_prob	rec_prob. Default value = 0.8
mut_prob	mut_prob. Default value = 0.1
copy_prob	copy_prob. Default value = 0.01
alpha	alpha. Default value = 0.9
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```

data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::Falco_GP_C(data_train, data_test)
algorithm <- RKEEL::Falco_GP_C(data_train, data_test, population_size = 5, max_generations = 10)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions

```

FCRA_C

*FCRA_C KEEL Classification Algorithm***Description**

FCRA_C Classification Algorithm from KEEL.

Usage

```

FCRA_C(train, test, generations, pop_size, length_S_C, WCAR,
        WV, crossover_prob, mut_prob, n1, n2, max_iter,
        linguistic_values, seed)

```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
generations	generations. Default value = 50
pop_size	pop_size. Default value = 30
length_S_C	length_S_C. Default value = 10
WCAR	WCAR. Default value = 10.0
WV	WV. Default value = 1.0
crossover_prob	crossover_prob. Default value = 1.0
mut_prob	mut_prob. Default value = 0.01
n1	n1. Default value = 0.001
n2	n2. Default value = 0.1
max_iter	max_iter. Default value = 100
linguistic_values	linguistic_values. Default value = 5
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::FCRA_C(data_train, data_test, generations=10, pop_size=10)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

 FPgrowth_A

FPgrowth_A KEEL Association Rules Algorithm

Description

FPgrowth_A Association Rules Algorithm from KEEL.

Usage

```
FPgrowth_A(dat, NumberofPartitionsforNumericAttributes, MinimumSupport,
  MinimumConfidence)
```

Arguments

dat Dataset as a data.frame object
 NumberofPartitionsforNumericAttributes
 Number of Partitions for Numeric Attributes. Default value = 4
 MinimumSupport Minimum Support. Default value = 0.1
 MinimumConfidence
 MinimumConfidence. Default value = 0.8

Details

\$run() Run algorithm

\$showRules(numRules) Show a number of rules. By default all rules.

\$getInterestMeasures() Return a data.frame with all interest measures of set rules.

`$sortBy(interestMeasure)` Order set rules by interest measure.

`$writeCSV(fileName, sep)` Create CSV file with set rules. Default `fileName="rules"` `sep=","`

`$writePMML(fileName)` Create PMML file with set rules. Default `fileName="rules"`

`$addInterestMeasure(name, colName)` Add interest measures to set rules. Some interest measures supported:

"allConfidence" (Omiencinski, 2003)

"crossSupportRatio", cross-support ratio (Xiong et al., 2003)

"lift", interest factor (Brin et al. 1997)

"support", supp (Agrawal et al., 1996)

"addedValue", added Value, AV, Pavillon index, centered confidence (Tan et al., 2002)

"chiSquared", X^2 (Liu et al., 1999)

"certainty", certainty factor, CF, Loevinger (Berzal et al., 2002)

"collectiveStrength"

"confidence", conf (Agrawal et al., 1996)

"conviction" (Brin et al. 1997)

"cosine" (Tan et al., 2004)

"coverage", cover, LHS-support

"confirmedConfidence", descriptive confirmed confidence (Kodratoff, 1999)

"casualConfidence", casual confidence (Kodratoff, 1999)

"casualSupport", casual support (Kodratoff, 1999)

"counterexample", example and counterexample rate

"descriptiveConfirm", descriptive-confirm (Kodratoff, 1999)

"doc", difference of confidence (Hofmann and Wilhelm, 2001)

"fishersExactTest", Fisher's exact test (Hahsler and Hornik, 2007)

"gini", Gini index (Tan et al., 2004)

"hyperLift" (Hahsler and Hornik, 2007)

"hyperConfidence" (Hahsler and Hornik, 2007)

"imbalance", imbalance ratio, IR (Wu, Chen and Han, 2010)

"implicationIndex", implication index (Gras, 1996)

"improvement" (Bayardo et al., 2000)

"jaccard", Jaccard coefficient (Tan and Kumar, 2000)

"jMeasure", J-measure, J (Smyth and Goodman, 1991)

"kappa" (Tan and Kumar, 2000)

"kloggen", Kloggen (Tan and Kumar, 2000)

"kulczynski" (Wu, Chen and Han, 2007; Kulczynski, 1927)

"lambda", Goodman-Kruskal lambda, predictive association (Tan and Kumar, 2000)

"laplace", L (Tan and Kumar 2000)

"leastContradiction", least contradiction (Aze and Kodratoff, 2004)

"lerman", Lerman similarity (Lerman, 1981)

"leverage", PS (Piatetsky-Shapiro 1991)

"mutualInformation", uncertainty, M (Tan et al., 2002)

"oddsRatio", odds ratio alpha (Tan et al., 2004)

"phi", correlation coefficient phi (Tan et al. 2004)

"ralambrodriainy", Ralambrodriainy Measure (Ralambrodriainy, 1991)

"RLD", relative linkage disequilibrium (Kenett and Salini, 2008)

"sebag", Sebag measure (Sebag and Schoenauer, 1988)

"support", supp (Agrawal et al., 1996)

"varyingLiaison", varying rates liaison (Bernard and Charron, 1996)

"yuleQ", Yule's Q (Tan and Kumar, 2000)

"yuleY", Yule's Y (Tan and Kumar, 2000)

For more information see ?arules::interestMeasure

Value

A arules class with the Association Rules for both dat dataset.

Examples

```
#Load KEEL dataset
dat<-RKEEL::loadKeelDataset("car")

#Create algorithm
algorithm <- RKEEL::FPgrowth_A(dat)

#Run algorithm
algorithm$run()

#Rules in format arules
algorithm$rules

#Show a number of rules
algorithm$showRules(2)

#Return a data.frame with all interest measures of set rules
algorithm$getInterestMeasures()

#Add interest measure YuleY to set rules
algorithm$addInterestMeasure("YuleY", "yulesY")

#Sort by interest measure lift
algorithm$sortBy("lift")

#Save rules in CSV file
algorithm$writeCSV(paste0(tempdir(), "/myrules"))
```

Description

FRNN_C Classification Algorithm from KEEL.

Usage

```
FRNN_C(train, test)
```

Arguments

```
train      Train dataset as a data.frame object
test       Test dataset as a data.frame object
```

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test  <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::FRNN_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

FRSBM_R

FRSBM_R KEEL Regression Algorithm

Description

FRSBM_R Regression Algorithm from KEEL.

Usage

```
FRSBM_R(train, test, numrules, sigma, seed)
```

Arguments

```
train      Train dataset as a data.frame object
test       Test dataset as a data.frame object
numrules   numrules. Default value = 1
sigma      sigma. Default value = 0.0001
seed       Seed for random numbers. If it is not assigned a value, the seed will be a random number
```

Value

A data.frame with the actual and predicted values for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("autoMPG6_train")
data_test <- RKEEL::loadKeelDataset("autoMPG6_test")

#Create algorithm
algorithm <- RKEEL::FRSBM_R(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

FURIA_C

FURIA_C KEEL Classification Algorithm

Description

FURIA_C Classification Algorithm from KEEL.

Usage

```
FURIA_C(train, test, optimizations, folds, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
optimizations	optimizations. Default value = 2
folds	folds. Default value = 3
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```

data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::FURIA_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions

```

FuzzyApriori_A

FuzzyApriori_A KEEL Association Rules Algorithm

Description

FuzzyApriori_A Association Rules Algorithm from KEEL.

Usage

```

FuzzyApriori_A(dat, NumberofPartitionsforNumericAttributes,
  UseMaxOperatorfor1FrequentItemsets, MinimumSupport, MinimumConfidence)

```

Arguments

dat Dataset as a data.frame object
NumberofPartitionsforNumericAttributes
 Number of Partitions for Numeric Attributes. Default value = 4
UseMaxOperatorfor1FrequentItemsets
 Use Max Operator for 1 Frequent Itemsets. Default value = "false"
MinimumSupport Minimum Support. Default value = 0.1
MinimumConfidence
 Minimum Confidence. Default value = 0.8

Details

\$run() Run algorithm
\$showRules(numRules) Show a number of rules. By default all rules.
\$getInterestMeasures() Return a data.frame with all interest measures of set rules.
\$sortBy(interestMeasure) Order set rules by interest measure.
\$writeCSV(fileName, sep) Create CSV file with set rules. Default fileName="rules" sep=","

`$writePMML(fileName)` Create PMML file with set rules. Default `fileName="rules"`

`$addInterestMeasure(name, colName)` Add interest measures to set rules. Some interest measures supported:

"allConfidence" (Omiencinski, 2003)

"crossSupportRatio", cross-support ratio (Xiong et al., 2003)

"lift", interest factor (Brin et al. 1997)

"support", supp (Agrawal et al., 1996)

"addedValue", added Value, AV, Pavillon index, centered confidence (Tan et al., 2002)

"chiSquared", X^2 (Liu et al., 1999)

"certainty", certainty factor, CF, Loevinger (Berzal et al., 2002)

"collectiveStrength"

"confidence", conf (Agrawal et al., 1996)

"conviction" (Brin et al. 1997)

"cosine" (Tan et al., 2004)

"coverage", cover, LHS-support

"confirmedConfidence", descriptive confirmed confidence (Kodratoff, 1999)

"casualConfidence", casual confidence (Kodratoff, 1999)

"casualSupport", casual support (Kodratoff, 1999)

"counterexample", example and counterexample rate

"descriptiveConfirm", descriptive-confirm (Kodratoff, 1999)

"doc", difference of confidence (Hofmann and Wilhelm, 2001)

"fishersExactTest", Fisher's exact test (Hahsler and Hornik, 2007)

"gini", Gini index (Tan et al., 2004)

"hyperLift" (Hahsler and Hornik, 2007)

"hyperConfidence" (Hahsler and Hornik, 2007)

"imbalance", imbalance ratio, IR (Wu, Chen and Han, 2010)

"implicationIndex", implication index (Gras, 1996)

"improvement" (Bayardo et al., 2000)

"jaccard", Jaccard coefficient (Tan and Kumar, 2000)

"jMeasure", J-measure, J (Smyth and Goodman, 1991)

"kappa" (Tan and Kumar, 2000)

"kloggen", Kloggen (Tan and Kumar, 2000)

"kulczynski" (Wu, Chen and Han, 2007; Kulczynski, 1927)

"lambda", Goodman-Kruskal lambda, predictive association (Tan and Kumar, 2000)

"laplace", L (Tan and Kumar 2000)

"leastContradiction", least contradiction (Aze and Kodratoff, 2004)

"lerman", Lerman similarity (Lerman, 1981)

"leverage", PS (Piatetsky-Shapiro 1991)

"mutualInformation", uncertainty, M (Tan et al., 2002)

"oddsRatio", odds ratio alpha (Tan et al., 2004)

"phi", correlation coefficient phi (Tan et al. 2004)

"ralambrodriainy", Ralambrodriainy Measure (Ralambrodriainy, 1991)

"RLD", relative linkage disequilibrium (Kenett and Salini, 2008)

"sebag", Sebag measure (Sebag and Schoenauer, 1988)

"support", supp (Agrawal et al., 1996)

"varyingLiaison", varying rates liaison (Bernard and Charron, 1996)

"yuleQ", Yule's Q (Tan and Kumar, 2000)

"yuleY", Yule's Y (Tan and Kumar, 2000)

For more information see ?arules::interestMeasure

Value

A arules class with the Association Rules for both dat dataset.

Examples

```
#Load KEEL dataset
dat<-RKEEL::loadKeelDataset("car")

#Create algorithm
algorithm <- RKEEL::FuzzyApriori_A(dat)

#Run algorithm
algorithm$run()

#Rules in format arules
algorithm$rules

#Show a number of rules
algorithm$showRules(2)

#Return a data.frame with all interest measures of set rules
algorithm$getInterestMeasures()

#Add interest measure YuleY to set rules
algorithm$addInterestMeasure("YuleY", "yulesY")

#Sort by interest measure lift
algorithm$sortBy("lift")

#Save rules in CSV file
algorithm$writeCSV(paste0(tempdir(), "/myrules"))
```

FuzzyFARCHD_C

FuzzyFARCHD_C KEEL Classification Algorithm

Description

FuzzyFARCHD_C Classification Algorithm from KEEL.

Usage

```
FuzzyFARCHD_C(train, test, linguistic_values, min_support,
  max_confidence, depth_max, K, max_evaluations, pop_size,
  alpha, bits_per_gen, inference_type, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
linguistic_values	linguistic_values. Default value = 5
min_support	min_support. Default value = 0.05
max_confidence	max_confidence. Default value = 0.8
depth_max	depth_max. Default value = 3
K	K. Default value = 2
max_evaluations	max_evaluations. Default value = 15000
pop_size	pop_size. Default value = 50
alpha	alpha. Default value = 0.15
bits_per_gen	bits_per_gen. Default value = 30
inference_type	inference_type. Default value = 1
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::FuzzyFARCHD_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

FuzzyKNN_C

FuzzyKNN_C KEEL Classification Algorithm

Description

FuzzyKNN_C Classification Algorithm from KEEL.

Usage

```
FuzzyKNN_C(train, test, k, M, initialization, init_k)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
k	k. Default value = 3
M	M. Default value = 2.0
initialization	initialization. Default value = "CRISP"
init_k	init_k. Default value = 3

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::FuzzyKNN_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

FuzzyNPC_C

FuzzyNPC_C KEEL Classification Algorithm

Description

FuzzyNPC_C Classification Algorithm from KEEL.

Usage

```
FuzzyNPC_C(train, test, M)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
M	M. Default value = 2.0

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::FuzzyNPC_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

GANN_C

GANN_C KEEL Classification Algorithm

Description

GANN_C Classification Algorithm from KEEL.

Usage

```
GANN_C(train, test, hidden_layers, hidden_nodes, transfer, eta,
        alpha, lambda, test_data, validation_data, cross_validation,
        BP_cycles, improve, tipify_inputs, save_all, elite,
        num_individuals, w_range, connectivity, P_bp, P_param,
        P_struct, max_generations, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
hidden_layers	hidden_layers. Default value = 2
hidden_nodes	hidden_nodes. Default value = 15
transfer	transfer. Default value = "Htan"
eta	eta. Default value = 0.15
alpha	alpha. Default value = 0.1
lambda	lambda. Default value = 0.0
test_data	test_data. Default value = TRUE
validation_data	validation_data. Default value = FALSE

```
cross_validation      cross_validation. Default value = FALSE
BP_cycles             BP_cycles. Default value = 10000
improve              improve. Default value = 0.01
tipify_inputs        tipify_inputs. Default value = TRUE
save_all             save_all. Default value = FALSE
elite                elite. Default value = 0.1
num_individuals      num_individuals. Default value = 100
w_range              w_range. Default value = 5.0
connectivity         connectivity. Default value = 0.5
P_bp                 P_bp. Default value = 0.25
P_param              P_param. Default value = 0.1
P_struct             P_struct. Default value = 0.1
max_generations      max_generations. Default value = 100
seed                 Seed for random numbers. If it is not assigned a value, the seed will be a random
                    number
```

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test  <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::GANN_C(data_train, data_test, hidden_layers=1,
  hidden_nodes=5, max_generations=5)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

GAR_A

*GAR_A KEEL Association Rules Algorithm***Description**

GAR_A Association Rules Algorithm from KEEL.

Usage

```
GAR_A(dat, seed, NumberofItemsets, TotalNumberofEvaluations, PopulationSize,
      ProbabilityofSelection, ProbabilityofCrossover, ProbabilityofMutation,
      ImportanceofNumberofRecordsAlreadyCovered, ImportanceofIntervalsAmplitude,
      ImportanceofNumberofInvolvedAttributes, AmplitudeFactor, MinimumSupport,
      MinimumConfidence)
```

Arguments

dat	Dataset as a data.frame object
seed	seed. Default value = 1286082570
NumberofItemsets	Number of Itemsets. Default value = 100
TotalNumberofEvaluations	Total Number of Evaluations. Default value = 50000
PopulationSize	Population Size. Default value = 100
ProbabilityofSelection	Probability of Selection. Default value = 0.25
ProbabilityofCrossover	Probability of Crossover. Default value = 0.7
ProbabilityofMutation	Probability of Mutation. Default value = 0.1
ImportanceofNumberofRecordsAlreadyCovered	Importance of Number of Records Already Covered. Default value = 0.4
ImportanceofIntervalsAmplitude	Importance of Intervals Amplitude. Default value = 0.7
ImportanceofNumberofInvolvedAttributes	Importance of Number of Involved Attributes. Default value = 0.5
AmplitudeFactor	Amplitude Factor. Default value = 2.0
MinimumSupport	Minimum Support. Default value = 0.1
MinimumConfidence	Minimum Confidence. Default value = 0.8

Details

`$run()` Run algorithm

`$showRules(numRules)` Show a number of rules. By default all rules.

`$getInterestMeasures()` Return a data.frame with all interest measures of set rules.

`$sortBy(interestMeasure)` Order set rules by interest measure.

`$writeCSV(fileName, sep)` Create CSV file with set rules. Default `fileName="rules"` `sep=","`

`$writePMML(fileName)` Create PMML file with set rules. Default `fileName="rules"`

`$addInterestMeasure(name, colName)` Add interest measures to set rules. Some interest measures supported:

"allConfidence" (Omiencinski, 2003)

"crossSupportRatio", cross-support ratio (Xiong et al., 2003)

"lift", interest factor (Brin et al. 1997)

"support", supp (Agrawal et al., 1996)

"addedValue", added Value, AV, Pavillon index, centered confidence (Tan et al., 2002)

"chiSquared", X^2 (Liu et al., 1999)

"certainty", certainty factor, CF, Loevinger (Berzal et al., 2002)

"collectiveStrength"

"confidence", conf (Agrawal et al., 1996)

"conviction" (Brin et al. 1997)

"cosine" (Tan et al., 2004)

"coverage", cover, LHS-support

"confirmedConfidence", descriptive confirmed confidence (Kodratoff, 1999)

"casualConfidence", casual confidence (Kodratoff, 1999)

"casualSupport", casual support (Kodratoff, 1999)

"counterexample", example and counterexample rate

"descriptiveConfirm", descriptive-confirm (Kodratoff, 1999)

"doc", difference of confidence (Hofmann and Wilhelm, 2001)

"fishersExactTest", Fisher's exact test (Hahsler and Hornik, 2007)

"gini", Gini index (Tan et al., 2004)

"hyperLift" (Hahsler and Hornik, 2007)

"hyperConfidence" (Hahsler and Hornik, 2007)

"imbalance", imbalance ratio, IR (Wu, Chen and Han, 2010)

"implicationIndex", implication index (Gras, 1996)

"improvement" (Bayardo et al., 2000)

"jaccard", Jaccard coefficient (Tan and Kumar, 2000)

"jMeasure", J-measure, J (Smyth and Goodman, 1991)

"kappa" (Tan and Kumar, 2000)

"kloggen", Kloggen (Tan and Kumar, 2000)

"kulczynski" (Wu, Chen and Han, 2007; Kulczynski, 1927)

"lambda", Goodman-Kruskal lambda, predictive association (Tan and Kumar, 2000)

"laplace", L (Tan and Kumar 2000)

"leastContradiction", least contradiction (Aze and Kodratoff, 2004)

"lerman", Lerman similarity (Lerman, 1981)

"leverage", PS (Piatetsky-Shapiro 1991)

"mutualInformation", uncertainty, M (Tan et al., 2002)

"oddsRatio", odds ratio alpha (Tan et al., 2004)

"phi", correlation coefficient phi (Tan et al. 2004)

"ralambrodriainy", Ralambrodriainy Measure (Ralambrodriainy, 1991)

"RLD", relative linkage disequilibrium (Kenett and Salini, 2008)

"sebag", Sebag measure (Sebag and Schoenauer, 1988)

"support", supp (Agrawal et al., 1996)

"varyingLiaison", varying rates liaison (Bernard and Charron, 1996)

"yuleQ", Yule's Q (Tan and Kumar, 2000)

"yuleY", Yule's Y (Tan and Kumar, 2000)

For more information see ?arules::interestMeasure

Value

A arules class with the Association Rules for both dat dataset.

Examples

```
#Load KEEL dataset
dat<-RKEEL::loadKeelDataset("glass")

#Create algorithm
algorithm <- RKEEL::GAR_A(dat)

#Run algorithm
algorithm$run()

#Rules in format arules
algorithm$rules

#Show a number of rules
algorithm$showRules(2)

#Return a data.frame with all interest measures of set rules
algorithm$getInterestMeasures()

#Add interest measure YuleY to set rules
algorithm$addInterestMeasure("YuleY", "yulesY")

#Sort by interest measure lift
algorithm$sortBy("lift")

#Save rules in CSV file
algorithm$writeCSV(paste0(tempdir(), "/myrules"))
```

 GENAR_A

GENAR_A KEEL Association Rules Algorithm

Description

GENAR_A Association Rules Algorithm from KEEL.

Usage

```
GENAR_A(dat, seed, NumberOfAssociationRules, TotalNumberOfEvaluations,
        PopulationSize, ProbabilityofSelection, ProbabilityofMutation,
        PenalizationFactor, AmplitudeFactor)
```

Arguments

dat	Dataset as a data.frame object
seed	seed. Default value = 1286082570
NumberOfAssociationRules	Number of Association Rules. Default value = 30
TotalNumberOfEvaluations	Total Number of Evaluations. Default value = 50000
PopulationSize	Population Size. Default value = 100
ProbabilityofSelection	Probability of Selection. Default value = 0.25
ProbabilityofMutation	Probability of Mutation. Default value = 0.1
PenalizationFactor	Penalization Factor. Default value = 0.7
AmplitudeFactor	Amplitude Factor. Default value = 2.0

Details

`$run()` Run algorithm

`$showRules(numRules)` Show a number of rules. By default all rules.

`$getInterestMeasures()` Return a data.frame with all interest measures of set rules.

`$sortBy(interestMeasure)` Order set rules by interest measure.

`$writeCSV(fileName, sep)` Create CSV file with set rules. Default fileName="rules" sep=" , "

`$writePMML(fileName)` Create PMML file with set rules. Default fileName="rules"

`$addInterestMeasure(name, colName)` Add interest measures to set rules. Some interest measures supported:

"allConfidence" (Omiencinski, 2003)

"crossSupportRatio", cross-support ratio (Xiong et al., 2003)

"lift", interest factor (Brin et al. 1997)

"support", supp (Agrawal et al., 1996)

"addedValue", added Value, AV, Pavillon index, centered confidence (Tan et al., 2002)

"chiSquared", X^2 (Liu et al., 1999)

"certainty", certainty factor, CF, Loevinger (Berzal et al., 2002)

"collectiveStrength"

"confidence", conf (Agrawal et al., 1996)

"conviction" (Brin et al. 1997)

"cosine" (Tan et al., 2004)

"coverage", cover, LHS-support

"confirmedConfidence", descriptive confirmed confidence (Kodratoff, 1999)

"casualConfidence", casual confidence (Kodratoff, 1999)

"casualSupport", casual support (Kodratoff, 1999)

"counterexample", example and counterexample rate

"descriptiveConfirm", descriptive-confirm (Kodratoff, 1999)

"doc", difference of confidence (Hofmann and Wilhelm, 2001)

"fishersExactTest", Fisher's exact test (Hahsler and Hornik, 2007)

"gini", Gini index (Tan et al., 2004)

"hyperLift" (Hahsler and Hornik, 2007)

"hyperConfidence" (Hahsler and Hornik, 2007)

"imbalance", imbalance ratio, IR (Wu, Chen and Han, 2010)

"implicationIndex", implication index (Gras, 1996)

"improvement" (Bayardo et al., 2000)

"jaccard", Jaccard coefficient (Tan and Kumar, 2000)

"jMeasure", J-measure, J (Smyth and Goodman, 1991)

"kappa" (Tan and Kumar, 2000)

"kloggen", Kloggen (Tan and Kumar, 2000)

"kulczynski" (Wu, Chen and Han, 2007; Kulczynski, 1927)

"lambda", Goodman-Kruskal lambda, predictive association (Tan and Kumar, 2000)

"laplace", L (Tan and Kumar 2000)

"leastContradiction", least contradiction (Aze and Kodratoff, 2004)

"lerman", Lerman similarity (Lerman, 1981)

"leverage", PS (Piatetsky-Shapiro 1991)

"mutualInformation", uncertainty, M (Tan et al., 2002)

"oddsRatio", odds ratio alpha (Tan et al., 2004)

"phi", correlation coefficient phi (Tan et al. 2004)

"ralambrodriainy", Ralambrodriainy Measure (Ralambrodriainy, 1991)

"RLD", relative linkage disequilibrium (Kenett and Salini, 2008)

"sebag", Sebag measure (Sebag and Schoenauer, 1988)

"support", supp (Agrawal et al., 1996)

"varyingLiaison", varying rates liaison (Bernard and Charron, 1996)

"yuleQ", Yule's Q (Tan and Kumar, 2000)

"yuleY", Yule's Y (Tan and Kumar, 2000)

For more information see ?arules::interestMeasure

Value

A arules class with the Association Rules for both dat dataset.

Examples

```
#Load KEEL dataset
dat<-RKEEL::loadKeelDataset("glass")

#Create algorithm
algorithm <- RKEEL::GENAR_A(dat)

#Run algorithm
algorithm$run()

#Rules in format arules
algorithm$rules

#Show a number of rules
algorithm$showRules(2)

#Return a data.frame with all interest measures of set rules
algorithm$getInterestMeasures()

#Add interest measure YuleY to set rules
algorithm$addInterestMeasure("YuleY", "yulesY")

#Sort by interest measure lift
algorithm$sortBy("lift")

#Save rules in CSV file
algorithm$writeCSV(paste0(tempdir(), "/myrules"))
```

GeneticFuzzyAprioriDC_A

GeneticFuzzyAprioriDC_A KEEL Association Rules Algorithm

Description

GeneticFuzzyAprioriDC_A Association Rules Algorithm from KEEL.

Usage

```
GeneticFuzzyAprioriDC_A(dat, seed, NumberofEvaluations, PopulationSize,
  ProbabilityofMutation, ProbabilityofCrossover, ParameterdforMMACrossover,
  NumberofFuzzyRegionsforNumericAttributes, UseMaxOperatorfor1FrequentItemsets,
  MinimumSupport, MinimumConfidence)
```

Arguments

<code>dat</code>	Dataset as a data.frame object
<code>seed</code>	seed. Default value = 1286082570
<code>NumberOfEvaluations</code>	Number of Evaluations. Default value = 10000
<code>PopulationSize</code>	Population Size. Default value = 50
<code>ProbabilityofMutation</code>	Probability of Mutation. Default value = 0.01
<code>ProbabilityofCrossover</code>	Probability of Crossover. Default value = 0.8
<code>ParameterdforMMACrossover</code>	Parameterd for MMA Crossover. Default value = 0.35
<code>NumberOfFuzzyRegionsforNumericAttributes</code>	Number of Fuzzy Regions for Numeric Attributes. Default value = 3
<code>UseMaxOperatorfor1FrequentItemsets</code>	Use Max Operator for 1 Frequent Itemsets. Default value = "false"
<code>MinimumSupport</code>	Minimum Support. Default value = 0.1
<code>MinimumConfidence</code>	Minimum Confidence. Default value = 0.8

Details

`$run()` Run algorithm

`$showRules(numRules)` Show a number of rules. By default all rules.

`$getInterestMeasures()` Return a data.frame with all interest measures of set rules.

`$sortBy(interestMeasure)` Order set rules by interest measure.

`$writeCSV(fileName, sep)` Create CSV file with set rules. Default `fileName="rules"` `sep=","`

`$writePMML(fileName)` Create PMML file with set rules. Default `fileName="rules"`

`$addInterestMeasure(name, colName)` Add interest measures to set rules. Some interest measures supported:

"allConfidence" (Omiencinski, 2003)

"crossSupportRatio", cross-support ratio (Xiong et al., 2003)

"lift", interest factor (Brin et al. 1997)

"support", supp (Agrawal et al., 1996)

"addedValue", added Value, AV, Pavillon index, centered confidence (Tan et al., 2002)

"chiSquared", X^2 (Liu et al., 1999)

"certainty", certainty factor, CF, Loevinger (Berzal et al., 2002)

"collectiveStrength"

"confidence", conf (Agrawal et al., 1996)

"conviction" (Brin et al. 1997)

"cosine" (Tan et al., 2004)

"coverage", cover, LHS-support

"confirmedConfidence", descriptive confirmed confidence (Kodratoff, 1999)

"casualConfidence", casual confidence (Kodratoff, 1999)

"casualSupport", casual support (Kodratoff, 1999)

"counterexample", example and counterexample rate

"descriptiveConfirm", descriptive-confirm (Kodratoff, 1999)

"doc", difference of confidence (Hofmann and Wilhelm, 2001)

"fishersExactTest", Fisher's exact test (Hahsler and Hornik, 2007)

"gini", Gini index (Tan et al., 2004)

"hyperLift" (Hahsler and Hornik, 2007)

"hyperConfidence" (Hahsler and Hornik, 2007)

"imbalance", imbalance ratio, IR (Wu, Chen and Han, 2010)

"implicationIndex", implication index (Gras, 1996)

"improvement" (Bayardo et al., 2000)

"jaccard", Jaccard coefficient (Tan and Kumar, 2000)

"jMeasure", J-measure, J (Smyth and Goodman, 1991)

"kappa" (Tan and Kumar, 2000)

"klosgen", Klosgen (Tan and Kumar, 2000)

"kulczynski" (Wu, Chen and Han, 2007; Kulczynski, 1927)

"lambda", Goodman-Kruskal lambda, predictive association (Tan and Kumar, 2000)

"laplace", L (Tan and Kumar 2000)

"leastContradiction", least contradiction (Aze and Kodratoff, 2004)

"lerman", Lerman similarity (Lerman, 1981)

"leverage", PS (Piatetsky-Shapiro 1991)

"mutualInformation", uncertainty, M (Tan et al., 2002)

"oddsRatio", odds ratio alpha (Tan et al., 2004)

"phi", correlation coefficient phi (Tan et al. 2004)

"ralambrodriainy", Ralambrodriainy Measure (Ralambrodriainy, 1991)

"RLD", relative linkage disequilibrium (Kenett and Salini, 2008)

"sebag", Sebag measure (Sebag and Schoenauer, 1988)

"support", supp (Agrawal et al., 1996)

"varyingLiaison", varying rates liaison (Bernard and Charron, 1996)

"yuleQ", Yule's Q (Tan and Kumar, 2000)

"yuleY", Yule's Y (Tan and Kumar, 2000)

For more information see ?arules::interestMeasure

Value

A arules class with the Association Rules for both dat dataset.

Examples

```
#Load KEEL dataset
dat<-RKEEL::loadKeelDataset("car")

#Create algorithm
algorithm <- RKEEL::GeneticFuzzyAprioriDC_A(dat)
```

```

#Run algorithm
algorithm$run()

#Rules in format arules
algorithm$rules

#Show a number of rules
algorithm$showRules(2)

#Return a data.frame with all interest measures of set rules
algorithm$getInterestMeasures()

#Add interest measure YuleY to set rules
algorithm$addInterestMeasure("YuleY", "yulesY")

#Sort by interest measure lift
algorithm$sortBy("lift")

#Save rules in CSV file
algorithm$writeCSV(paste0(tempdir(), "/myrules"))

```

GeneticFuzzyApriori_A *GeneticFuzzyApriori_A KEEL Association Rules Algorithm*

Description

GeneticFuzzyApriori_A Association Rules Algorithm from KEEL.

Usage

```

GeneticFuzzyApriori_A(dat, seed, NumberofEvaluations, PopulationSize,
  ProbabilityofMutation, ProbabilityofCrossover, ParameterdforMMACrossover,
  NumberofFuzzyRegionsforNumericAttributes, UseMaxOperatorfor1FrequentItemsets,
  MinimumSupport, MinimumConfidence)

```

Arguments

dat	Dataset as a data.frame object
seed	seed. Default value = 1286082570
NumberofEvaluations	Number of Evaluations. Default value = 10000
PopulationSize	Population Size. Default value = 50
ProbabilityofMutation	Probability of Mutation. Default value = 0.01
ProbabilityofCrossover	Probability of Crossover. Default value = 0.8

ParameterdforMMACrossover
 Parameterd for MMA Crossover. Default value = 0.35

NumberOfFuzzyRegionsforNumericAttributes
 Number of Fuzzy Regions for Numeric Attributes. Default value = 3

UseMaxOperatorfor1FrequentItemsets
 Use Max Operator for 1 Frequent Itemsets. Default value = "false"

MinimumSupport Minimum Support. Default value = 0.1

MinimumConfidence
 Minimum Confidence. Default value = 0.8

Details

`$run()` Run algorithm

`$showRules(numRules)` Show a number of rules. By default all rules.

`$getInterestMeasures()` Return a data.frame with all interest measures of set rules.

`$sortBy(interestMeasure)` Order set rules by interest measure.

`$writeCSV(fileName, sep)` Create CSV file with set rules. Default `fileName="rules"` `sep=","`

`$writePMML(fileName)` Create PMML file with set rules. Default `fileName="rules"`

`$addInterestMeasure(name, colName)` Add interest measures to set rules. Some interest measures supported:

"allConfidence" (Omiencinski, 2003)

"crossSupportRatio", cross-support ratio (Xiong et al., 2003)

"lift", interest factor (Brin et al. 1997)

"support", supp (Agrawal et al., 1996)

"addedValue", added Value, AV, Pavillon index, centered confidence (Tan et al., 2002)

"chiSquared", X^2 (Liu et al., 1999)

"certainty", certainty factor, CF, Loevinger (Berzal et al., 2002)

"collectiveStrength"

"confidence", conf (Agrawal et al., 1996)

"conviction" (Brin et al. 1997)

"cosine" (Tan et al., 2004)

"coverage", cover, LHS-support

"confirmedConfidence", descriptive confirmed confidence (Kodratoff, 1999)

"casualConfidence", casual confidence (Kodratoff, 1999)

"casualSupport", casual support (Kodratoff, 1999)

"counterexample", example and counterexample rate

"descriptiveConfirm", descriptive-confirm (Kodratoff, 1999)

"doc", difference of confidence (Hofmann and Wilhelm, 2001)

"fishersExactTest", Fisher's exact test (Hahsler and Hornik, 2007)

"gini", Gini index (Tan et al., 2004)

"hyperLift" (Hahsler and Hornik, 2007)

"hyperConfidence" (Hahsler and Hornik, 2007)

"imbalance", imbalance ratio, IR (Wu, Chen and Han, 2010)

"implicationIndex", implication index (Gras, 1996)

"improvement" (Bayardo et al., 2000)

"jaccard", Jaccard coefficient (Tan and Kumar, 2000)

"jMeasure", J-measure, J (Smyth and Goodman, 1991)

"kappa" (Tan and Kumar, 2000)

"klogen", Klogen (Tan and Kumar, 2000)

"kulczynski" (Wu, Chen and Han, 2007; Kulczynski, 1927)

"lambda", Goodman-Kruskal lambda, predictive association (Tan and Kumar, 2000)

"laplace", L (Tan and Kumar 2000)

"leastContradiction", least contradiction (Aze and Kodratoff, 2004)

"lerman", Lerman similarity (Lerman, 1981)

"leverage", PS (Piatetsky-Shapiro 1991)

"mutualInformation", uncertainty, M (Tan et al., 2002)

"oddsRatio", odds ratio alpha (Tan et al., 2004)

"phi", correlation coefficient phi (Tan et al. 2004)

"ralambrodrainy", Ralambrodrainy Measure (Ralambrodrainy, 1991)

"RLD", relative linkage disequilibrium (Kenett and Salini, 2008)

"sebag", Sebag measure (Sebag and Schoenauer, 1988)

"support", supp (Agrawal et al., 1996)

"varyingLiaison", varying rates liaison (Bernard and Charron, 1996)

"yuleQ", Yule's Q (Tan and Kumar, 2000)

"yuleY", Yule's Y (Tan and Kumar, 2000)

For more information see ?arules::interestMeasure

Value

A arules class with the Association Rules for both dat dataset.

Examples

```
#Load KEEL dataset
dat<-RKEEL::loadKeelDataset("car")

#Create algorithm
algorithm <- RKEEL::GeneticFuzzyApriori_A(dat)

#Run algorithm
algorithm$run()

#Rules in format arules
algorithm$rules

#Show a number of rules
algorithm$showRules(2)

#Return a data.frame with all interest measures of set rules
algorithm$getInterestMeasures()
```

```
#Add interest measure YuleY to set rules
algorithm$addInterestMeasure("YuleY", "yulesY")

#Sort by interest measure lift
algorithm$sortBy("lift")

#Save rules in CSV file
algorithm$writeCSV(paste0(tempdir(), "/myrules"))
```

getAttributeLinesFromDataframes

Get attribute lines from data.frames

Description

Method for getting the attribute lines from data.frame objects

Usage

```
getAttributeLinesFromDataframes(trainData, testData)
```

Arguments

trainData	Train dataset as data.frame
testData	Test dataset as data.frame

Value

Returns a list with the attribute names and types

Examples

```
iris_train <- RKEEL::loadKeelDataset("iris_train")
iris_test <- RKEEL::loadKeelDataset("iris_test")

attributeLines <- getAttributeLinesFromDataframes(iris_train, iris_test)
```

`getExePath`*Get jar executable files Path*

Description

Method for knowing the KEEL .jar files path.

Usage

```
getExePath()
```

Value

Returns a string with the path of the KEEL .jar files.

Examples

```
getExePath()
```

`getJarList`*Get a list with all RKEEL algorithm jars*

Description

Method that returns a list with the jar names from RKEEL

Usage

```
getJarList()
```

Value

Returns a list with the jar names from RKEEL.

Examples

```
getJarList()
```

getJarPath	<i>Get RunKeel.jar Path</i>
------------	-----------------------------

Description

Method for knowing the RunKeel.jar path.

Usage

```
getJarPath()
```

Value

Returns a string with the RunKeel.jar path.

Examples

```
getJarPath()
```

GFS_AdaBoost_C	<i>GFS_AdaBoost_C KEEL Classification Algorithm</i>
----------------	---

Description

GFS_AdaBoost_C Classification Algorithm from KEEL.

Usage

```
GFS_AdaBoost_C(train, test, numLabels, numRules, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
numLabels	numLabels. Default value = 3
numRules	numRules. Default value = 8
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```

data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::GFS_AdaBoost_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions

```

GFS_GP_R

GFS_GP_R KEEL Regression Algorithm

Description

GFS_GP_R Regression Algorithm from KEEL.

Usage

```

GFS_GP_R(train, test, numLabels, numRules, popSize, numisland,
  steady, numIter, tourSize, mutProb, aplMut, probMigra,
  probOptimLocal, numOptimLocal, idOptimLocal, nichinggap,
  maxindniche, probintraniche, probcrosssga, probmutaga,
  lenchaingap, maxtreeheight, seed)

```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
numLabels	numLabels. Default value = 3
numRules	numRules. Default value = 8
popSize	popSize. Default value = 30
numisland	numisland. Default value = 2
steady	steady. Default value = 1
numIter	numIter. Default value = 100
tourSize	tourSize. Default value = 4
mutProb	mutProb. Default value = 0.01
aplMut	aplMut. Default value = 0.1
probMigra	probMigra. Default value = 0.001
probOptimLocal	probOptimLocal. Default value = 0.00

numOptimLocal	numOptimLocal. Default value = 0
idOptimLocal	idOptimLocal. Default value = 0
nichinggap	nichinggap. Default value = 0
maxindniche	maxindniche. Default value = 8
probintranche	probintranche. Default value = 0.75
probcrossga	probcrossga. Default value = 0.5
probmutaga	probmutaga. Default value = 0.5
lenchaingap	lenchaingap. Default value = 10
maxtreeheight	maxtreeheight. Default value = 8
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted values for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("autoMPG6_train")
data_test <- RKEEL::loadKeelDataset("autoMPG6_test")

#Create algorithm
algorithm <- RKEEL::GFS_GP_R(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

GFS_GSP_R

GFS_GSP_R KEEL Regression Algorithm

Description

GFS_GSP_R Regression Algorithm from KEEL.

Usage

```
GFS_GSP_R(train, test, numLabels, numRules, deltafitsap,
  p0sap, p1sap, amplMut, nsubsap, probOptimLocal,
  numOptimLocal, idOptimLocal, probcrossga, probmutaga,
  lenchaingap, maxtreeheight, numItera, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
numLabels	numLabels. Default value = 3
numRules	numRules. Default value = 8
deltafitsap	deltafitsap. Default value = 0.5
p0sap	p0sap. Default value = 0.5
p1sap	p1sap. Default value = 0.5
amplMut	amplMut. Default value = 0.1
nsubsap	nsubsap. Default value = 10
probOptimLocal	probOptimLocal. Default value = 0.00
numOptimLocal	numOptimLocal. Default value = 0
idOptimLocal	idOptimLocal. Default value = 0
probcrossga	probcrossga. Default value = 0.5
probmutaga	probmutaga. Default value = 0.5
lenchaingap	lenchaingap. Default value = 10
maxtreeheight	maxtreeheight. Default value = 8
numItera	numItera. Default value = 10000
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted values for both train and test datasets.

Examples

```

data_train <- RKEEL::loadKeelDataset("autoMPG6_train")
data_test <- RKEEL::loadKeelDataset("autoMPG6_test")

#Create algorithm
algorithm <- RKEEL::GFS_GSP_R(data_train, data_test)
algorithm <- RKEEL::GFS_GSP_R(data_train, data_test, numRules=2, numItera=10, maxtreeheight=2)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions

```

GFS_LogitBoost_C *GFS_LogitBoost_C KEEL Classification Algorithm*

Description

GFS_LogitBoost_C Classification Algorithm from KEEL.

Usage

```
GFS_LogitBoost_C(train, test, numLabels, numRules, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
numLabels	numLabels. Default value = 3
numRules	numRules. Default value = 25
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::GFS_LogitBoost_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

GFS_RB_MF_R

GFS_RB_MF_R KEEL Regression Algorithm

Description

GFS_RB_MF_R Regression Algorithm from KEEL.

Usage

```
GFS_RB_MF_R(train, test, numLabels, popSize, generations,
             crossProb, mutProb, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
numLabels	numLabels. Default value = 3
popSize	popSize. Default value = 50
generations	generations. Default value = 100
crossProb	crossProb. Default value = 0.9
mutProb	mutProb. Default value = 0.1
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted values for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("autoMPG6_train")
data_test <- RKEEL::loadKeelDataset("autoMPG6_test")

#Create algorithm
algorithm <- RKEEL::GFS_RB_MF_R(data_train, data_test)
algorithm <- RKEEL::GFS_RB_MF_R(data_train, data_test, popSize = 5, generations = 10)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

hasContinuousData	<i>Has Continuous Data</i>
-------------------	----------------------------

Description

Method for check if a dataset has continuous data

Usage

```
hasContinuousData(data)
```

Arguments

data	Dataset as data.frame
------	-----------------------

Value

Returns TRUE if the dataset has continuous data and FALSE if it has not.

Examples

```
iris <- RKEEL::loadKeelDataset("iris")
hasContinuousData(iris)
```

hasMissingValues	<i>Has Missing Values</i>
------------------	---------------------------

Description

Method for check if a dataset has missing values

Usage

```
hasMissingValues(data)
```

Arguments

data	Dataset as data.frame
------	-----------------------

Value

Returns TRUE if the dataset has missing values and FALSE if it has not.

Examples

```
iris <- RKEEL::loadKeelDataset("iris")
hasMissingValues(iris)
```

ID3_C

ID3_C KEEL Classification Algorithm

Description

ID3_C Classification Algorithm from KEEL.

Usage

```
ID3_C(train, test)
```

Arguments

<code>train</code>	Train dataset as a data.frame object
<code>test</code>	Test dataset as a data.frame object

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::ID3_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

ID3_D

ID3_D KEEL Preprocess Algorithm

Description

ID3_D Preprocess Algorithm from KEEL.

Usage

```
ID3_D(train, test)
```


Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::ID3_D(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$preprocessed_test
```

IF_KNN_C

*IF_KNN_C KEEL Classification Algorithm***Description**

IF_KNN_C Classification Algorithm from KEEL.

Usage

```
IF_KNN_C(train, test, K, mA, vA, mR, vR, k)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
K	K. Default value = 3
mA	mA. Default value = 0.6
vA	vA. Default value = 0.4
mR	mR. Default value = 0.3
vR	vR. Default value = 0.7
k	k. Default value = 5

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::IF_KNN_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

 Ignore_MV

Ignore_MV KEEL Preprocess Algorithm

Description

Ignore_MV Preprocess Algorithm from KEEL.

Usage

```
Ignore_MV(train, test)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::Ignore_MV(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$preprocessed_test
```

ImbalancedClassificationAlgorithm
ImbalancedClassification Algorithm

Description

Class inheriting of ClassificationAlgorithm, to common methods for all KEEL Imbalanced Classification Algorithms. The specific imbalanced-classification algorithms must inherit of this class.

IncrRBFN_C *IncrRBFN_C KEEL Classification Algorithm*

Description

IncrRBFN_C Classification Algorithm from KEEL.

Usage

```
IncrRBFN_C(train, test, epsilon, alfa, delta, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
epsilon	epsilon. Default value = 0.1
alfa	alfa. Default value = 0.3
delta	delta. Default value = 0.5
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::IncrRBFN_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

isMultiClass	<i>Is Multi-class</i>
--------------	-----------------------

Description

Method for check if a dataset is multi-class

Usage

```
isMultiClass(data)
```

Arguments

data	Dataset as data.frame
------	-----------------------

Value

Returns TRUE if the dataset is multi-class and FALSE if it is not.

Examples

```
iris <- RKEEL::loadKeelDataset("iris")
isMultiClass(iris)
```

IterativePartitioningFilter_F

IterativePartitioningFilter_F KEEL Preprocess Algorithm

Description

IterativePartitioningFilter_F Preprocess Algorithm from KEEL.

Usage

```
IterativePartitioningFilter_F(train, test, numPartitions,
  filterType, confidence, itemsetsPerLeaf, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
numPartitions	numPartitions. Default value = 5
filterType	filterType. Default value = "consensus"
confidence	confidence. Default value = 0.25
itemsetsPerLeaf	itemsetsPerLeaf. Default value = 2
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::IterativePartitioningFilter_F(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$preprocessed_test
```

JFKNN_C

JFKNN_C KEEL Classification Algorithm

Description

JFKNN_C Classification Algorithm from KEEL.

Usage

```
JFKNN_C(train, test)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::JFKNN_C(data_train, data_test)

#Run algorithm
algorithm$run()
```

```
#See results
algorithm$testPredictions
```

KeelAlgorithm	<i>Keel Algorithm</i>
---------------	-----------------------

Description

Principal class for implementing KEEL Algorithms. The distinct types of algorithms must inherit of this class.

Kernel_C	<i>Kernel_C KEEL Classification Algorithm</i>
----------	---

Description

Kernel_C Classification Algorithm from KEEL.

Usage

```
Kernel_C(train, test, sigma, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
sigma	sigma. Default value = 0.01
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::Kernel_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

`KMeans_MV`*KMeans_MV KEEL Preprocess Algorithm*

Description

KMeans_MV Preprocess Algorithm from KEEL.

Usage

```
KMeans_MV(train, test, k, error, iterations, seed)
```

Arguments

<code>train</code>	Train dataset as a data.frame object
<code>test</code>	Test dataset as a data.frame object
<code>k</code>	k. Default value = 10
<code>error</code>	error. Default value = 100
<code>iterations</code>	iterations. Default value = 100
<code>seed</code>	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::KMeans_MV(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$preprocessed_test
```

KNN_C*KNN-C KEEL Classification Algorithm*

Description

KNN-C Classification Algorithm from KEEL.

Usage

```
KNN_C(train, test, k, distance)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
k	Number of neighbors
distance	Distance function

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::KNN_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

KNN_MV*KNN_MV KEEL Preprocess Algorithm*

Description

KNN_MV Preprocess Algorithm from KEEL.

Usage

```
KNN_MV(train, test, k)
```


Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
k	k. Default value = 10

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::KNN_MV(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$preprocessed_test
```

KSNN_C

KSNN_C KEEL Classification Algorithm

Description

KSNN_C Classification Algorithm from KEEL.

Usage

```
KSNN_C(train, test, k)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
k	k. Default value = 1

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```

data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::KSNN_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions

```

KStar_C

KStar_C KEEL Classification Algorithm

Description

KStar_C Classification Algorithm from KEEL.

Usage

```
KStar_C(train, test, selection_method, blend, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
selection_method	selection_method. Default value = "Fixed"
blend	blend. Default value = 0.2
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```

data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::KStar_C(data_train, data_test)

#Run algorithm

```

```
algorithm$run()

#See results
algorithm$testPredictions
```

LDA_C

LDA_C KEEL Classification Algorithm

Description

LDA_C Classification Algorithm from KEEL.

Usage

```
LDA_C(train, test, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::LDA_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

LinearLMS_C

LinearLMS_C KEEL Classification Algorithm

Description

LinearLMS_C Classification Algorithm from KEEL.

Usage

```
LinearLMS_C(train, test, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::LinearLMS_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

LinearLMS_R

LinearLMS_R KEEL Regression Algorithm

Description

LinearLMS_R Regression Algorithm from KEEL.

Usage

```
LinearLMS_R(train, test, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted values for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("autoMPG6_train")
data_test <- RKEEL::loadKeelDataset("autoMPG6_test")

#Create algorithm
algorithm <- RKEEL::LinearLMS_R(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

loadKeelDataset	<i>Load KEEL Dataset</i>
-----------------	--------------------------

Description

Loads a dataset of the KEEL datasets repository. The included datasets names are available at the getKeelDatasetList method of RKEELdata.

Usage

```
loadKeelDataset(dataName)
```

Arguments

dataName	String with the correct data name of one of the KEEL datasets
----------	---

Value

Returns a data.frame with the KEEL dataset.

Examples

```
RKEEL::loadKeelDataset("iris")
```

Logistic_C

Logistic_C KEEL Classification Algorithm

Description

Logistic_C Classification Algorithm from KEEL.

Usage

```
Logistic_C(train, test, ridge, maxIter)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
ridge	ridge. Default value = 1e-8
maxIter	maxIter. Default value = -1

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::Logistic_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

LVF_IEP_FS

LVF_IEP_FS KEEL Preprocess Algorithm

Description

LVF_IEP_FS Preprocess Algorithm from KEEL.

Usage

```
LVF_IEP_FS(train, test, paramKNN, maxLoops, inconAllow, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
paramKNN	paramKNN. Default value = 1
maxLoops	maxLoops. Default value = 770
inconAllow	inconAllow. Default value = 0
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::LVF_IEP_FS(data_train, data_test)
algorithm <- RKEEL::LVF_IEP_FS(data_train, data_test, maxLoops = 30,
  inconAllow=2)

#Run algorithm
algorithm$run()

#See results
algorithm$preprocessed_test
```

M5Rules_R

M5Rules_R KEEL Regression Algorithm

Description

M5Rules_R Regression Algorithm from KEEL.

Usage

```
M5Rules_R(train, test, pruningFactor, heuristic)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
pruningFactor	pruningFactor. Default value = 2
heuristic	heuristic. Default value = "Coverage"

Value

A data.frame with the actual and predicted values for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("autoMPG6_train")
data_test <- RKEEL::loadKeelDataset("autoMPG6_test")

#Create algorithm
algorithm <- RKEEL::M5Rules_R(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

M5_R

M5_R KEEL Regression Algorithm

Description

M5_R Regression Algorithm from KEEL.

Usage

```
M5_R(train, test, type, pruningFactor, unsmoothed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
type	type. Default value = "m"
pruningFactor	pruningFactor. Default value = 2
unsmoothed	unsmoothed. Default value = TRUE

Value

A data.frame with the actual and predicted values for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("autoMPG6_train")
data_test <- RKEEL::loadKeelDataset("autoMPG6_test")

#Create algorithm
algorithm <- RKEEL::M5_R(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

MinMax_TR

MinMax_TR KEEL Preprocess Algorithm

Description

MinMax_TR Preprocess Algorithm from KEEL.

Usage

```
MinMax_TR(train, test, newMin, newMax)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
newMin	newMin. Default value = 0.0
newMax	newMax. Default value = 1.0

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::MinMax_TR(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$preprocessed_test
```

MLP_BP_C

*MLP_BP_C KEEL Classification Algorithm***Description**

MLP_BP_C Classification Algorithm from KEEL.

Usage

```
MLP_BP_C(train, test, hidden_layers, hidden_nodes, transfer,
eta, alpha, lambda, test_data, validation_data,
cross_validation, cycles, improve, tipify_inputs,
save_all, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
hidden_layers	hidden_layers. Default value = 2
hidden_nodes	hidden_nodes. Default value = 15
transfer	transfer. Default value = "Htan"
eta	eta. Default value = 0.15
alpha	alpha. Default value = 0.1
lambda	lambda. Default value = 0.0
test_data	test_data. Default value = TRUE
validation_data	validation_data. Default value = FALSE
cross_validation	cross_validation. Default value = FALSE
cycles	cycles. Default value = 10000
improve	improve. Default value = 0.01
tipify_inputs	tipify_inputs. Default value = TRUE
save_all	save_all. Default value = FALSE
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```

data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::MLP_BP_C(data_train, data_test, )

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions

```

MLP_BP_R

*MLP_BP_R KEEL Regression Algorithm***Description**

MLP_BP_R Regression Algorithm from KEEL.

Usage

```

MLP_BP_R(train, test, hidden_layers, hidden_nodes, transfer,
eta, alpha, lambda, test_data, validation_data,
cross_validation, cycles, improve, tipify_inputs,
save_all, seed)

```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
hidden_layers	hidden_layers. Default value = 2
hidden_nodes	hidden_nodes. Default value = 15
transfer	transfer. Default value = "Htan"
eta	eta. Default value = 0.15
alpha	alpha. Default value = 0.1
lambda	lambda. Default value = 0.0
test_data	test_data. Default value = TRUE
validation_data	validation_data. Default value = FALSE
cross_validation	cross_validation. Default value = FALSE
cycles	cycles. Default value = 10000

improve	improve. Default value = 0.01
tipify_inputs	tipify_inputs. Default value = TRUE
save_all	save_all. Default value = FALSE
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted values for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("autoMPG6_train")
data_test <- RKEEL::loadKeelDataset("autoMPG6_test")

#Create algorithm
algorithm <- RKEEL::MLP_BP_R(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

ModelCS_TSS

ModelCS_TSS KEEL Preprocess Algorithm

Description

ModelCS_TSS Preprocess Algorithm from KEEL.

Usage

```
ModelCS_TSS(train, test, k, distance)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
k	k. Default value = 3
distance	distance. Default value = "Euclidean"

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```

data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::ModelCS_TSS(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$preprocessed_test

```

MODENAR_A

MODENAR_A KEEL Association Rules Algorithm

Description

MODENAR_A Association Rules Algorithm from KEEL.

Usage

```

MODENAR_A(dat, seed, PopulationSize, NumberofEvaluations, CrossoverrateCR,
  Thresholdforthenumberofnondominationsolutions,
  Thefactorofamplitudeforeachattributeofthedataset, WeightforSupport,
  WeightforConfidence, WeightforComprehensibility,
  WeightforAmplitudeoftheIntervals)

```

Arguments

dat	Dataset as a data.frame object
seed	seed. Default value = 1286082570
PopulationSize	Population Size. Default value = 100
NumberofEvaluations	Number of Evaluations. Default value = 50000
CrossoverrateCR	Crossover rate CR. Default value = 0.3
Thresholdforthenumberofnondominationsolutions	Threshold for the number of non-dominated solutions. Default value = 60
Thefactorofamplitudeforeachattributeofthedataset	The factor of amplitude for each attribute of the dataset. Default value = 2
WeightforSupport	Weight for Support. Default value = 0.8
WeightforConfidence	Weight for Confidence. Default value = 0.2

WeightforComprehensibility

Weight for Comprehensibility. Default value = 0.1

WeightforAmplitudeoftheIntervals

Weight for Amplitude of the Intervals. Default value = 0.4

Details

`$run()` Run algorithm

`$showRules(numRules)` Show a number of rules. By default all rules.

`$getInterestMeasures()` Return a data.frame with all interest measures of set rules.

`$sortBy(interestMeasure)` Order set rules by interest measure.

`$writeCSV(fileName, sep)` Create CSV file with set rules. Default `fileName="rules"` `sep=","`

`$writePMML(fileName)` Create PMML file with set rules. Default `fileName="rules"`

`$addInterestMeasure(name, colName)` Add interest measures to set rules. Some interest measures supported:

"allConfidence" (Omiencinski, 2003)

"crossSupportRatio", cross-support ratio (Xiong et al., 2003)

"lift", interest factor (Brin et al. 1997)

"support", supp (Agrawal et al., 1996)

"addedValue", added Value, AV, Pavillon index, centered confidence (Tan et al., 2002)

"chiSquared", X^2 (Liu et al., 1999)

"certainty", certainty factor, CF, Loevinger (Berzal et al., 2002)

"collectiveStrength"

"confidence", conf (Agrawal et al., 1996)

"conviction" (Brin et al. 1997)

"cosine" (Tan et al., 2004)

"coverage", cover, LHS-support

"confirmedConfidence", descriptive confirmed confidence (Kodratoff, 1999)

"casualConfidence", casual confidence (Kodratoff, 1999)

"casualSupport", casual support (Kodratoff, 1999)

"counterexample", example and counterexample rate

"descriptiveConfirm", descriptive-confirm (Kodratoff, 1999)

"doc", difference of confidence (Hofmann and Wilhelm, 2001)

"fishersExactTest", Fisher's exact test (Hahsler and Hornik, 2007)

"gini", Gini index (Tan et al., 2004)

"hyperLift" (Hahsler and Hornik, 2007)

"hyperConfidence" (Hahsler and Hornik, 2007)

"imbalance", imbalance ratio, IR (Wu, Chen and Han, 2010)

"implicationIndex", implication index (Gras, 1996)

"improvement" (Bayardo et al., 2000)

"jaccard", Jaccard coefficient (Tan and Kumar, 2000)

"jMeasure", J-measure, J (Smyth and Goodman, 1991)

"kappa" (Tan and Kumar, 2000)

"kloggen", Kloggen (Tan and Kumar, 2000)

"kulczynski" (Wu, Chen and Han, 2007; Kulczynski, 1927)

"lambda", Goodman-Kruskal lambda, predictive association (Tan and Kumar, 2000)

"laplace", L (Tan and Kumar 2000)

"leastContradiction", least contradiction (Aze and Kodratoff, 2004)

"lerman", Lerman similarity (Lerman, 1981)

"leverage", PS (Piatetsky-Shapiro 1991)

"mutualInformation", uncertainty, M (Tan et al., 2002)

"oddsRatio", odds ratio alpha (Tan et al., 2004)

"phi", correlation coefficient phi (Tan et al. 2004)
"ralambrodrainy", Ralambrodrainy Measure (Ralambrodrainy, 1991)
"RLD", relative linkage disequilibrium (Kenett and Salini, 2008)
"sebag", Sebag measure (Sebag and Schoenauer, 1988)
"support", supp (Agrawal et al., 1996)
"varyingLiaison", varying rates liaison (Bernard and Charron, 1996)
"yuleQ", Yule's Q (Tan and Kumar, 2000)
"yuleY", Yule's Y (Tan and Kumar, 2000)
For more information see ?arules::interestMeasure

Value

A arules class with the Association Rules for both dat dataset.

Examples

```
#Load KEEL dataset
dat<-RKEEL::loadKeelDataset("car")

#Create algorithm
algorithm <- RKEEL::MODENAR_A(dat)

#Run algorithm
algorithm$run()

#Rules in format arules
algorithm$rules

#Show a number of rules
algorithm$showRules(2)

#Return a data.frame with all interest measures of set rules
algorithm$getInterestMeasures()

#Add interst measure YuleY to set rules
algorithm$addInterestMeasure("YuleY", "yulesY")

#Sort by interest measure lift
algorithm$sortBy("lift")
```



```
#Save rules in CSV file
algorithm$writeCSV(paste0(tempdir(), "/myrules"))
```

MOEA_Ghosh_A

MOEA_Ghosh_A KEEL Association Rules Algorithm

Description

MOEA_Ghosh_A Association Rules Algorithm from KEEL.

Usage

```
MOEA_Ghosh_A(dat, seed, NumberofObjectives, NumberofEvaluations, PopulationSize,
  PointCrossover, ProbabilityofCrossover, ProbabilityofMutation,
  Thefactorofamplitudeforeachattributeofthedataset)
```

Arguments

dat	Dataset as a data.frame object
seed	seed. Default value = 1286082570
NumberofObjectives	Number of Objectives. Default value = 3
NumberofEvaluations	Number of Evaluations. Default value = 50000
PopulationSize	Population Size. Default value = 100
PointCrossover	Point Crossover. Default value = 2
ProbabilityofCrossover	Probability of Crossover. Default value = 0.8
ProbabilityofMutation	Probability of Mutation. Default value = 0.02
Thefactorofamplitudeforeachattributeofthedataset	The factor of amplitude for each attribute of the dataset. Default value = 2.0

Details

`$run()` Run algorithm

`$showRules(numRules)` Show a number of rules. By default all rules.

`$getInterestMeasures()` Return a data.frame with all interest measures of set rules.

`$sortBy(interestMeasure)` Order set rules by interest measure.

`$writeCSV(fileName, sep)` Create CSV file with set rules. Default fileName="rules" sep=","

`$writePMML(fileName)` Create PMML file with set rules. Default `fileName="rules"`

`$addInterestMeasure(name, colName)` Add interest measures to set rules. Some interest measures supported:

"allConfidence" (Omiencinski, 2003)

"crossSupportRatio", cross-support ratio (Xiong et al., 2003)

"lift", interest factor (Brin et al. 1997)

"support", supp (Agrawal et al., 1996)

"addedValue", added Value, AV, Pavillon index, centered confidence (Tan et al., 2002)

"chiSquared", X^2 (Liu et al., 1999)

"certainty", certainty factor, CF, Loevinger (Berzal et al., 2002)

"collectiveStrength"

"confidence", conf (Agrawal et al., 1996)

"conviction" (Brin et al. 1997)

"cosine" (Tan et al., 2004)

"coverage", cover, LHS-support

"confirmedConfidence", descriptive confirmed confidence (Kodratoff, 1999)

"casualConfidence", casual confidence (Kodratoff, 1999)

"casualSupport", casual support (Kodratoff, 1999)

"counterexample", example and counterexample rate

"descriptiveConfirm", descriptive-confirm (Kodratoff, 1999)

"doc", difference of confidence (Hofmann and Wilhelm, 2001)

"fishersExactTest", Fisher's exact test (Hahsler and Hornik, 2007)

"gini", Gini index (Tan et al., 2004)

"hyperLift" (Hahsler and Hornik, 2007)

"hyperConfidence" (Hahsler and Hornik, 2007)

"imbalance", imbalance ratio, IR (Wu, Chen and Han, 2010)

"implicationIndex", implication index (Gras, 1996)

"improvement" (Bayardo et al., 2000)

"jaccard", Jaccard coefficient (Tan and Kumar, 2000)

"jMeasure", J-measure, J (Smyth and Goodman, 1991)

"kappa" (Tan and Kumar, 2000)

"klogen", Klogen (Tan and Kumar, 2000)

"kulczynski" (Wu, Chen and Han, 2007; Kulczynski, 1927)

"lambda", Goodman-Kruskal lambda, predictive association (Tan and Kumar, 2000)

"laplace", L (Tan and Kumar 2000)

"leastContradiction", least contradiction (Aze and Kodratoff, 2004)

"lerman", Lerman similarity (Lerman, 1981)

"leverage", PS (Piatetsky-Shapiro 1991)

"mutualInformation", uncertainty, M (Tan et al., 2002)

"oddsRatio", odds ratio alpha (Tan et al., 2004)

"phi", correlation coefficient phi (Tan et al. 2004)

"ralambrodriainy", Ralambrodriainy Measure (Ralambrodriainy, 1991)

"RLD", relative linkage disequilibrium (Kenett and Salini, 2008)

"sebag", Sebag measure (Sebag and Schoenauer, 1988)

"support", supp (Agrawal et al., 1996)

"varyingLiaison", varying rates liaison (Bernard and Charron, 1996)

"yuleQ", Yule's Q (Tan and Kumar, 2000)

"yuleY", Yule's Y (Tan and Kumar, 2000)

For more information see `?arules::interestMeasure`

Value

A `arules` class with the Association Rules for both `dat` dataset.

Examples

```
#Load KEEL dataset
dat<-RKEEL::loadKeelDataset("car")

#Create algorithm
algorithm <- RKEEL::MOEA_Ghosh_A(dat)

#Run algorithm
algorithm$run()

#Rules in format arules
algorithm$rules

#Show a number of rules
algorithm$showRules(2)

#Return a data.frame with all interest measures of set rules
algorithm$getInterestMeasures()

#Add interest measure YuleY to set rules
algorithm$addInterestMeasure("YuleY", "yulesY")

#Sort by interest measure lift
algorithm$sortBy("lift")

#Save rules in CSV file
algorithm$writeCSV(paste0(tempdir(), "/myrules"))
```

MOPNAR_A

MOPNAR_A KEEL Association Rules Algorithm

Description

MOPNAR_A Association Rules Algorithm from KEEL.

Usage

```
MOPNAR_A(dat, seed, objectives, evaluations, parameter, weightNeighborhood,
          wprobabilitySolutionsNeighborhood, maxSolutions, probabilityMutation,
          amplitude, threshold)
```

Arguments

dat	Dataset as a data.frame object
seed	seed. Default value = 1286082570
objectives	objectives. Default value = 3
evaluations	evaluations. Default value = 50000
parameter	parameter. Default value = 13
weightNeighborhood	weightNeighborhood. Default value = 10
wprobabilitySolutionsNeighborhood	wprobabilitySolutionsNeighborhood. Default value = 0.9
maxSolutions	maxSolutions. Default value = 2
probabilityMutation	probabilityMutation. Default value = 0.1
amplitude	amplitude. Default value = 2.0
threshold	threshold. Default value = 5.0

Details

`$run()` Run algorithm

`$showRules(numRules)` Show a number of rules. By default all rules.

`$getInterestMeasures()` Return a data.frame with all interest measures of set rules.

`$sortBy(interestMeasure)` Order set rules by interest measure.

`$writeCSV(fileName, sep)` Create CSV file with set rules. Default fileName="rules" sep=","

`$writePMML(fileName)` Create PMML file with set rules. Default fileName="rules"

`$addInterestMeasure(name, colName)` Add interest measures to set rules. Some interest measures supported:

"allConfidence" (Omiencinski, 2003)

"crossSupportRatio", cross-support ratio (Xiong et al., 2003)

"lift", interest factor (Brin et al. 1997)

"support", supp (Agrawal et al., 1996)

"addedValue", added Value, AV, Pavillon index, centered confidence (Tan et al., 2002)

"chiSquared", X^2 (Liu et al., 1999)

"certainty", certainty factor, CF, Loevinger (Berzal et al., 2002)

"collectiveStrength"

"confidence", conf (Agrawal et al., 1996)

"conviction" (Brin et al. 1997)

"cosine" (Tan et al., 2004)

"coverage", cover, LHS-support

"confirmedConfidence", descriptive confirmed confidence (Kodratoff, 1999)

"casualConfidence", casual confidence (Kodratoff, 1999)

"casualSupport", casual support (Kodratoff, 1999)

"counterexample", example and counterexample rate

"descriptiveConfirm", descriptive-confirm (Kodratoff, 1999)

"doc", difference of confidence (Hofmann and Wilhelm, 2001)

"fishersExactTest", Fisher's exact test (Hahsler and Hornik, 2007)

"gini", Gini index (Tan et al., 2004)

"hyperLift" (Hahsler and Hornik, 2007)

"hyperConfidence" (Hahsler and Hornik, 2007)

"imbalance", imbalance ratio, IR (Wu, Chen and Han, 2010)

"implicationIndex", implication index (Gras, 1996)

"improvement" (Bayardo et al., 2000)

"jaccard", Jaccard coefficient (Tan and Kumar, 2000)

"jMeasure", J-measure, J (Smyth and Goodman, 1991)

"kappa" (Tan and Kumar, 2000)

"klosgen", Klosgen (Tan and Kumar, 2000)

"kulczynski" (Wu, Chen and Han, 2007; Kulczynski, 1927)

"lambda", Goodman-Kruskal lambda, predictive association (Tan and Kumar, 2000)

"laplace", L (Tan and Kumar 2000)

"leastContradiction", least contradiction (Aze and Kodratoff, 2004)

"lerman", Lerman similarity (Lerman, 1981)

"leverage", PS (Piatetsky-Shapiro 1991)

"mutualInformation", uncertainty, M (Tan et al., 2002)

"oddsRatio", odds ratio alpha (Tan et al., 2004)

"phi", correlation coefficient phi (Tan et al. 2004)

"ralambrodriainy", Ralambrodriainy Measure (Ralambrodriainy, 1991)

"RLD", relative linkage disequilibrium (Kenett and Salini, 2008)

"sebag", Sebag measure (Sebag and Schoenauer, 1988)

"support", supp (Agrawal et al., 1996)

"varyingLiaison", varying rates liaison (Bernard and Charron, 1996)

"yuleQ", Yule's Q (Tan and Kumar, 2000)

"yuleY", Yule's Y (Tan and Kumar, 2000)

For more information see ?arules::interestMeasure

Value

A arules class with the Association Rules for both dat dataset.

Examples

```
#Load KEEL dataset
```

```
dat<-RKEEL::loadKeelDataset("car")

#Create algorithm
algorithm <- RKEEL::MOPNAR_A(dat)

#Run algorithm
algorithm$run()

#Rules in format arules
algorithm$rules

#Show a number of rules
algorithm$showRules(2)

#Return a data.frame with all interest measures of set rules
algorithm$getInterestMeasures()

#Add interest measure YuleY to set rules
algorithm$addInterestMeasure("YuleY", "yulesY")

#Sort by interest measure lift
algorithm$sortBy("lift")

#Save rules in CSV file
algorithm$writeCSV(paste0(tempdir(), "/myrules"))
```

MostCommon_MV

MostCommon_MV KEEL Preprocess Algorithm

Description

MostCommon_MV Preprocess Algorithm from KEEL.

Usage

```
MostCommon_MV(train, test)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::MostCommon_MV(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$preprocessed_test
```

NB_C

NB_C KEEL Classification Algorithm

Description

NB_C Classification Algorithm from KEEL.

Usage

```
NB_C(train, test)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::NB_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

 NICGAR_A

NICGAR_A KEEL Association Rules Algorithm

Description

NICGAR_A Association Rules Algorithm from KEEL.

Usage

```
NICGAR_A(dat, seed, NumberofEvaluations, PopulationSize, ProbabilityofMutation,
  Thefactorofamplitudeforeachattributeofthedataset, NichingThreshold,
  QualityThreshold, PercentUpdate)
```

Arguments

dat	Dataset as a data.frame object
seed	seed. Default value = 1286082570
NumberofEvaluations	Number of Evaluations. Default value = 1286082570
PopulationSize	Population Size. Default value = 1286082570
ProbabilityofMutation	Probability of Mutation. Default value = 1286082570
Thefactorofamplitudeforeachattributeofthedataset	The factor of amplitude for each attribute of the dataset. Default value = 1286082570
NichingThreshold	Niching Threshold. Default value = 1286082570
QualityThreshold	Quality Threshold. Default value = 1286082570
PercentUpdate	Percent Update. Default value = 1286082570

Details

`$run()` Run algorithm

`$showRules(numRules)` Show a number of rules. By default all rules.

`$getInterestMeasures()` Return a data.frame with all interest measures of set rules.

`$sortBy(interestMeasure)` Order set rules by interest measure.

`$writeCSV(fileName, sep)` Create CSV file with set rules. Default fileName="rules" sep=","

`$writePMML(fileName)` Create PMML file with set rules. Default fileName="rules"

`$addInterestMeasure(name, colName)` Add interest measures to set rules. Some interest measures supported:

"allConfidence" (Omiencinski, 2003)

"crossSupportRatio", cross-support ratio (Xiong et al., 2003)

"lift", interest factor (Brin et al. 1997)

"support", supp (Agrawal et al., 1996)

"addedValue", added Value, AV, Pavillon index, centered confidence (Tan et al., 2002)

"chiSquared", X^2 (Liu et al., 1999)

"certainty", certainty factor, CF, Loevinger (Berzal et al., 2002)

"collectiveStrength"

"confidence", conf (Agrawal et al., 1996)

"conviction" (Brin et al. 1997)

"cosine" (Tan et al., 2004)

"coverage", cover, LHS-support

"confirmedConfidence", descriptive confirmed confidence (Kodratoff, 1999)

"casualConfidence", casual confidence (Kodratoff, 1999)

"casualSupport", casual support (Kodratoff, 1999)

"counterexample", example and counterexample rate

"descriptiveConfirm", descriptive-confirm (Kodratoff, 1999)

"doc", difference of confidence (Hofmann and Wilhelm, 2001)

"fishersExactTest", Fisher's exact test (Hahsler and Hornik, 2007)

"gini", Gini index (Tan et al., 2004)

"hyperLift" (Hahsler and Hornik, 2007)

"hyperConfidence" (Hahsler and Hornik, 2007)

"imbalance", imbalance ratio, IR (Wu, Chen and Han, 2010)

"implicationIndex", implication index (Gras, 1996)

"improvement" (Bayardo et al., 2000)

"jaccard", Jaccard coefficient (Tan and Kumar, 2000)

"jMeasure", J-measure, J (Smyth and Goodman, 1991)

"kappa" (Tan and Kumar, 2000)

"klosgen", Klosgen (Tan and Kumar, 2000)

"kulczynski" (Wu, Chen and Han, 2007; Kulczynski, 1927)

"lambda", Goodman-Kruskal lambda, predictive association (Tan and Kumar, 2000)

"laplace", L (Tan and Kumar 2000)

"leastContradiction", least contradiction (Aze and Kodratoff, 2004)

"lerman", Lerman similarity (Lerman, 1981)

"leverage", PS (Piatetsky-Shapiro 1991)

"mutualInformation", uncertainty, M (Tan et al., 2002)

"oddsRatio", odds ratio alpha (Tan et al., 2004)

"phi", correlation coefficient phi (Tan et al. 2004)

"ralambrodriainy", Ralambrodriainy Measure (Ralambrodriainy, 1991)

"RLD", relative linkage disequilibrium (Kenett and Salini, 2008)

"sebag", Sebag measure (Sebag and Schoenauer, 1988)

"support", supp (Agrawal et al., 1996)

"varyingLiaison", varying rates liaison (Bernard and Charron, 1996)

"yuleQ", Yule's Q (Tan and Kumar, 2000)

"yuleY", Yule's Y (Tan and Kumar, 2000)

For more information see ?arules::interestMeasure

Value

A arules class with the Association Rules for both dat dataset.

Examples

```
#Load KEEL dataset
dat<-RKEEL::loadKeelDataset("car")

#Create algorithm
algorithm <- RKEEL::NICGAR_A(dat)

#Run algorithm
algorithm$run()

#Rules in format arules
algorithm$rules

#Show a number of rules
algorithm$showRules(2)

#Return a data.frame with all interest measures of set rules
algorithm$getInterestMeasures()

#Add interest measure YuleY to set rules
algorithm$addInterestMeasure("YuleY", "yulesY")

#Sort by interest measure lift
algorithm$sortBy("lift")

#Save rules in CSV file
algorithm$writeCSV(paste0(tempdir(), "/myrules"))
```

NM_C

NM_C KEEL Classification Algorithm

Description

NM_C Classification Algorithm from KEEL.

Usage

```
NM_C(train, test)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::NM_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

NNEP_C

NNEP_C KEEL Classification Algorithm

Description

NNEP_C Classification Algorithm from KEEL.

Usage

```
NNEP_C(train, test, hidden_nodes, transfer, generations, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
hidden_nodes	hidden_nodes. Default value = 4
transfer	transfer. Default value = "Product_Unit"
generations	generations. Default value = 200
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::NNEP_C(data_train, data_test)
algorithm <- RKEEL::NNEP_C(data_train, data_test, generations = 5)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

Nominal2Binary_TR

Nominal2Binary_TR KEEL Preprocess Algorithm

Description

Nominal2Binary_TR Preprocess Algorithm from KEEL.

Usage

```
Nominal2Binary_TR(train, test)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::Nominal2Binary_TR(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$preprocessed_test
```

 NU_SVM_C

NU_SVM_C KEEL Classification Algorithm

Description

NU_SVM_C Classification Algorithm from KEEL.

Usage

```
NU_SVM_C(train, test, KernelType, C, eps, degree, gamma, coef0,
          nu, p, shrinking, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
KernelType	KernelType. Default value = 1
C	C. Default value = "RBF"
eps	eps. Default value = 1000.0
degree	degree. Default value = 0.001
gamma	gamma. Default value = 10
coef0	coef0. Default value = 0.01
nu	nu. Default value = 0.1
p	p. Default value = 1.0
shrinking	shrinking. Default value = 1
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::NU_SVM_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

 NU_SVR_R

NU_SVR_R KEEL Regression Algorithm

Description

NU_SVR_R Regression Algorithm from KEEL.

Usage

```
NU_SVR_R(train, test, KernelType, C, eps, degree, gamma,
          coef0, nu, p, shrinking, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
KernelType	KernelType. Default value = ?
C	C. Default value = ?
eps	eps. Default value = ?
degree	degree. Default value = ?
gamma	gamma. Default value = ?
coef0	coef0. Default value = ?
nu	nu. Default value = ?
p	p. Default value = ?
shrinking	shrinking. Default value = ?
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted values for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("autoMPG6_train")
data_test <- RKEEL::loadKeelDataset("autoMPG6_test")

#Create algorithm
algorithm <- RKEEL::NU_SVR_R(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

 PART_C

PART_C KEEL Classification Algorithm

Description

PART_C Classification Algorithm from KEEL.

Usage

```
PART_C(train, test, confidence, itemsetsPerLeaf)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
confidence	confidence. Default value = 0.25
itemsetsPerLeaf	itemsetsPerLeaf. Default value = 2

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::PART_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

 PDFC_C

PDFC_C KEEL Classification Algorithm

Description

PDFC_C Classification Algorithm from KEEL.

Usage

```
PDFC_C(train, test, C, d, tolerance, epsilon, PDRFtype,  
        nominal_to_binary, preprocess_type, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
C	C. Default value = 100.0
d	d. Default value = 0.25
tolerance	tolerance. Default value = 0.001
epsilon	epsilon. Default value = 1.0E-12
PDRFtype	PDRFtype. Default value = "Gaussian"
nominal_to_binary	nominal_to_binary. Default value = TRUE
preprocess_type	preprocess_type. Default value = "Normalize"
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")  
data_test <- RKEEL::loadKeelDataset("iris_test")  
  
#Create algorithm  
algorithm <- RKEEL::PDFC_C(data_train, data_test)  
  
#Run algorithm  
algorithm$run()  
  
#See results  
algorithm$testPredictions
```

PFKNN_C

PFKNN_C KEEL Classification Algorithm

Description

PFKNN_C Classification Algorithm from KEEL.

Usage

```
PFKNN_C(train, test, k, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
k	k. Default value = 3
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::PFKNN_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

PNN_C

PNN_C KEEL Classification Algorithm

Description

PNN_C Classification Algorithm from KEEL.

Usage

```
PNN_C(train, test, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::PNN_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

PolQuadraticLMS_C *PolQuadraticLMS_C KEEL Classification Algorithm*

Description

PolQuadraticLMS_C Classification Algorithm from KEEL.

Usage

```
PolQuadraticLMS_C(train, test, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::PolQuadraticLMS_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

PolQuadraticLMS_R *PolQuadraticLMS_R KEEL Regression Algorithm*

Description

PolQuadraticLMS_R Regression Algorithm from KEEL.

Usage

```
PolQuadraticLMS_R(train, test, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted values for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("autoMPG6_train")
data_test <- RKEEL::loadKeelDataset("autoMPG6_test")

#Create algorithm
algorithm <- RKEEL::PolQuadraticLMS_R(data_train, data_test)

#Run algorithm
```

```
algorithm$run()

#See results
algorithm$testPredictions
```

POP_TSS

POP_TSS KEEL Preprocess Algorithm

Description

POP_TSS Preprocess Algorithm from KEEL.

Usage

```
POP_TSS(train, test)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::POP_TSS(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$preprocessed_test
```

PreprocessAlgorithm *Preprocess Algorithm*

Description

Class inheriting of KeelAlgorithm, to common methods for all KEEL Preprocess Algorithms. The specific preprocessing algorithms must inherit of this class.

The run() method receives three parameters. The folderPath parameter indicates where to place the folder with the experiments if wanted. If it is not indicated, the folder is placed in a temporary random directory and then removed. If indicated, the experiment folder is not removed. The expUniqueName parameter indicates the name of the experiment folder. If not indicated, it is a random name. If indicated, ensure that the name is unique in the previously indicated folder. The javaOptions parameter indicates, if wanted, extra parameters to the java command line, as for example the maximum memory allowed by java.

PRISM_C *PRISM_C KEEL Classification Algorithm*

Description

PRISM_C Classification Algorithm from KEEL.

Usage

```
PRISM_C(train, test, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::PRISM_C(data_train, data_test)
```



```
#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

Proportional_D *Proportional_D KEEL Preprocess Algorithm*

Description

Proportional_D Preprocess Algorithm from KEEL.

Usage

```
Proportional_D(train, test, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::Proportional_D(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$preprocessed_test
```

 PSO_ACO_C

PSO_ACO_C KEEL Classification Algorithm

Description

PSO_ACO_C Classification Algorithm from KEEL.

Usage

```
PSO_ACO_C(train, test, max_uncovered_samples, min_saples_by_rule,
  max_iterations_without_converge, enviromentSize, numParticles,
  x, c1, c2, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
max_uncovered_samples	max_uncovered_samples. Default value = 20
min_saples_by_rule	min_saples_by_rule. Default value = 2
max_iterations_without_converge	max_iterations_without_converge. Default value = 100
enviromentSize	enviromentSize. Default value = 3
numParticles	numParticles. Default value = 100
x	x. Default value = 0.72984
c1	c1. Default value = 2.05
c2	c2. Default value = 2.05
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::PSO_ACO_C(data_train, data_test,
  max_iterations_without_converge=2, numParticles=5)
```

```
#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

PSRCG_TSS

PSRCG_TSS KEEL Preprocess Algorithm

Description

PSRCG_TSS Preprocess Algorithm from KEEL.

Usage

```
PSRCG_TSS(train, test, distance)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
distance	distance. Default value = "Euclidean"

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::PSRCG_TSS(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$preprocessed_test
```

PUBLIC_C

PUBLIC_C KEEL Classification Algorithm

Description

PUBLIC_C Classification Algorithm from KEEL.

Usage

```
PUBLIC_C(train, test, nodesBetweenPrune, estimateToPrune)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
nodesBetweenPrune	nodesBetweenPrune. Default value = 25
estimateToPrune	estimateToPrune. Default value = "PUBLIC(1)"

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::PUBLIC_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

PW_C

PW_C KEEL Classification Algorithm

Description

PW_C Classification Algorithm from KEEL.

Usage

```
PW_C(train, test, beta, ro, epsilon)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
beta	beta. Default value = 8.0
ro	ro. Default value = 0.001
epsilon	epsilon. Default value = 0.001

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::PW_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

QAR_CIP_NSgaiI_A *QAR_CIP_NSgaiI_A KEEL Association Rules Algorithm*

Description

QAR_CIP_NSgaiI_A Association Rules Algorithm from KEEL.

Usage

```
QAR_CIP_NSgaiI_A(dat, seed, NumberOfObjectives, NumberOfEvaluations,
  PopulationSize, ProbabilityofMutation,
  Thefactorofamplitudeforeachattributeofthedataset, Differencethreshold)
```

Arguments

dat	Dataset as a data.frame object
seed	seed. Default value = 1286082570
NumberOfObjectives	Number of Objectives. Default value = 3
NumberOfEvaluations	Number of Evaluations. Default value = 50000
PopulationSize	Population Size. Default value = 100
ProbabilityofMutation	Probability of Mutation. Default value = 0.1
Thefactorofamplitudeforeachattributeofthedataset	The factor of amplitude for each attribute of the dataset. Default value = 2.0
Differencethreshold	Difference threshold. Default value = 5.0

Details

```
$run() Run algorithm

$showRules(numRules) Show a number of rules. By default all rules.

$getInterestMeasures() Return a data.frame with all interest measures of set rules.

$sortBy(interestMeasure) Order set rules by interest measure.

$writeCSV(fileName, sep) Create CSV file with set rules. Default fileName="rules" sep=","

$writePMML(fileName) Create PMML file with set rules. Default fileName="rules"

$addInterestMeasure(name, colName) Add interest measures to set rules. Some interest mea-
sures supported:
```

"allConfidence" (Omiencinski, 2003)

"crossSupportRatio", cross-support ratio (Xiong et al., 2003)

"lift", interest factor (Brin et al. 1997)

"support", supp (Agrawal et al., 1996)

"addedValue", added Value, AV, Pavillon index, centered confidence (Tan et al., 2002)

"chiSquared", X^2 (Liu et al., 1999)

"certainty", certainty factor, CF, Loevinger (Berzal et al., 2002)

"collectiveStrength"

"confidence", conf (Agrawal et al., 1996)

"conviction" (Brin et al. 1997)

"cosine" (Tan et al., 2004)

"coverage", cover, LHS-support

"confirmedConfidence", descriptive confirmed confidence (Kodratoff, 1999)

"casualConfidence", casual confidence (Kodratoff, 1999)

"casualSupport", casual support (Kodratoff, 1999)

"counterexample", example and counterexample rate

"descriptiveConfirm", descriptive-confirm (Kodratoff, 1999)

"doc", difference of confidence (Hofmann and Wilhelm, 2001)

"fishersExactTest", Fisher's exact test (Hahsler and Hornik, 2007)

"gini", Gini index (Tan et al., 2004)

"hyperLift" (Hahsler and Hornik, 2007)

"hyperConfidence" (Hahsler and Hornik, 2007)

"imbalance", imbalance ratio, IR (Wu, Chen and Han, 2010)

"implicationIndex", implication index (Gras, 1996)

"improvement" (Bayardo et al., 2000)

"jaccard", Jaccard coefficient (Tan and Kumar, 2000)

"jMeasure", J-measure, J (Smyth and Goodman, 1991)

"kappa" (Tan and Kumar, 2000)

"klosgen", Klosgen (Tan and Kumar, 2000)

"kulczynski" (Wu, Chen and Han, 2007; Kulczynski, 1927)

"lambda", Goodman-Kruskal lambda, predictive association (Tan and Kumar, 2000)

"laplace", L (Tan and Kumar 2000)

"leastContradiction", least contradiction (Aze and Kodratoff, 2004)

"lerman", Lerman similarity (Lerman, 1981)

"leverage", PS (Piatetsky-Shapiro 1991)

"mutualInformation", uncertainty, M (Tan et al., 2002)

"oddsRatio", odds ratio alpha (Tan et al., 2004)

"phi", correlation coefficient phi (Tan et al. 2004)

"ralambrodrainy", Ralambrodrainy Measure (Ralambrodrainy, 1991)

"RLD", relative linkage disequilibrium (Kenett and Salini, 2008)

"sebag", Sebag measure (Sebag and Schoenauer, 1988)

"support", supp (Agrawal et al., 1996)

"varyingLiaison", varying rates liaison (Bernard and Charron, 1996)

"yuleQ", Yule's Q (Tan and Kumar, 2000)

"yuleY", Yule's Y (Tan and Kumar, 2000)

For more information see ?arules::interestMeasure

Value

A arules class with the Association Rules for both dat dataset.

Examples

```
#Load KEEL dataset
dat<-RKEEL::loadKeelDataset("car")

#Create algorithm
algorithm <- RKEEL::QAR_CIP_NSGAII_A(dat)

#Run algorithm
algorithm$run()

#Rules in format arules
algorithm$rules

#Show a number of rules
algorithm$showRules(2)

#Return a data.frame with all interest measures of set rules
algorithm$getInterestMeasures()

#Add interest measure YuleY to set rules
algorithm$addInterestMeasure("YuleY", "yulesY")

#Sort by interest measure lift
algorithm$sortBy("lift")

#Save rules in CSV file
algorithm$writeCSV(paste0(tempdir(), "/myrules"))
```

QDA_C

QDA_C KEEL Classification Algorithm

Description

QDA_C Classification Algorithm from KEEL.

Usage

```
QDA_C(train, test, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object

seed Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::QDA_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

RBFN_C

RBFN_C KEEL Classification Algorithm

Description

RBFN_C Classification Algorithm from KEEL.

Usage

```
RBFN_C(train, test, neurons, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
neurons	neurons. Default value = 50
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```

data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::RBFN_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions

```

RBFN_R

*RBFN_R KEEL Regression Algorithm***Description**

RBFN_R Regression Algorithm from KEEL.

Usage

```
RBFN_R(train, test, neurons, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
neurons	neurons. Default value = 50
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted values for both train and test datasets.

Examples

```

data_train <- RKEEL::loadKeelDataset("autoMPG6_train")
data_test <- RKEEL::loadKeelDataset("autoMPG6_test")

#Create algorithm
algorithm <- RKEEL::RBFN_R(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions

```

read.keel	<i>Read keel dataset</i>
-----------	--------------------------

Description

Method for read datasets in .dat KEEL format

Usage

```
read.keel(file)
```

Arguments

file	File containing the dataset to be read. It must be in KEEL .dat format.
------	---

Value

Returns a data.frame object with the dataset

RegressionAlgorithm	<i>Regression Algorithm</i>
---------------------	-----------------------------

Description

Class inheriting of KeelAlgorithm, to common methods for all KEEL Regression Algorithms. The specific regression algorithms must inherit of this class.

The run() method receives three parameters. The folderPath parameter indicates where to place the folder with the experiments if wanted. If it is not indicated, the folder is placen ind a temporary random directory and then removed. If indicated, the experiment folder is not removed. The expUniqueName parameter indicates the name of the experiment folder. If not indicated, it is a random name. If indicated, ensure that the name is unique in the previously indicated folder. The javaOptions parameter indicates, if wanted, extra parameters to the java command line, as for example the maximum memory allowed by java.

RegressionResults	<i>Regression Results</i>
-------------------	---------------------------

Description

Class to calculate and store some results for a RegressionAlgorithm. It receives as parameter the prediction of a regression algorithm as a data.frame object.

Relief_FS

Relief_FS KEEL Preprocess Algorithm

Description

Relief_FS Preprocess Algorithm from KEEL.

Usage

```
Relief_FS(train, test, paramKNN, relevanceThreshold,  
          numInstancesSampled, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
paramKNN	paramKNN. Default value = 1
relevanceThreshold	relevanceThreshold. Default value = 0.20
numInstancesSampled	numInstancesSampled. Default value = 1000
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")  
data_test <- RKEEL::loadKeelDataset("car_test")  
  
#Create algorithm  
algorithm <- RKEEL::Relief_FS(data_train, data_test)  
  
#Run algorithm  
algorithm$run()  
  
#See results  
algorithm$preprocessed_test
```

Ripper_C*Ripper_C KEEL Classification Algorithm*

Description

Ripper_C Classification Algorithm from KEEL.

Usage

```
Ripper_C(train, test, grow_pct, k, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
grow_pct	grow_pct. Default value = 0.66
k	k. Default value = 2
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::Ripper_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

RISE_C	<i>RISE_C KEEL Classification Algorithm</i>
--------	---

Description

RISE_C Classification Algorithm from KEEL.

Usage

```
RISE_C(train, test, Q, S)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
Q	Q. Default value = 1
S	S. Default value = 2

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::RISE_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

runCV	<i>Run Cross-Validation</i>
-------	-----------------------------

Description

Run a cross-validation experiment

Usage

```
runCV(algorithm, dataset, numFolds, cores)
```

Arguments

algorithm	Algorithm to be executed in the CV. It must has the parameters to be used in the executions.
dataset	Dataset to perform the CV. It is divided in numFolds disjoint partitions and in each iteration, one is used for test and the rest for train.
numFolds	Number of folds for the cross-validation procedure.
cores	Number of cores to execute in parallel. If it is missed, default value is 1 (sequential execution).

Value

Returns a list with the mean results of the numFolds executions.

Examples

```
#Load datasets
iris <- RKEEL::loadKeelDataset("iris")

#Create algorithm
learner_C45_C <- RKEEL::C45_C(iris, iris)

#Perform 5-folds CV
results <- RKEEL::runCV(learner_C45_C, iris, 5)
```

runParallel

Run Parallel

Description

Run a set of RKEEL algorithms in parallel

Usage

```
runParallel(algorithmList, cores)
```

Arguments

algorithmList	List of RKEEL Algorithms to be executed
cores	Number of cores to execute in parallel. If it is not specified, it detects the cores automatically and execute the experiment in all of them

Value

Returns a list with the executed algorithms

Examples

```
#Load datasets
iris_train <- RKEEL::loadKeelDataset("iris_train")
iris_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithms
learner_C45_C <- RKEEL::C45_C(iris_train, iris_test)
learner_KNN_C <- RKEEL::KNN_C(iris_train, iris_test)
learner_Logistic_C <- RKEEL::Logistic_C(iris_train, iris_test)
learner_LDA_C <- RKEEL::LDA_C(iris_train, iris_test)

#Create list
algorithms <- list(learner_C45_C, learner_KNN_C, learner_Logistic_C,
  learner_LDA_C)

#Run algorithms in parallel in two cores
par <- RKEEL::runParallel(algorithms, 2)
```

`runSequential`*Run Sequential*

Description

Run a set of RKEEL algorithms in sequential.

Usage

```
runSequential(algorithmList)
```

Arguments

`algorithmList` List of RKEEL Algorithms to be executed

Value

Returns a list with the executed algorithms

Examples

```
#Load datasets
iris_train <- RKEEL::loadKeelDataset("iris_train")
iris_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithms
learner_C45_C <- RKEEL::C45_C(iris_train, iris_test)
learner_KNN_C <- RKEEL::KNN_C(iris_train, iris_test)
learner_Logistic_C <- RKEEL::Logistic_C(iris_train, iris_test)
learner_LDA_C <- RKEEL::LDA_C(iris_train, iris_test)
```

```
#Create list
algorithms <- list(learner_C45_C, learner_KNN_C, learner_Logistic_C,
  learner_LDA_C)

#Run algorithms
seq <- RKEEL::runSequential(algorithms)
```

SaturationFilter_F *SaturationFilter_F KEEL Preprocess Algorithm*

Description

SaturationFilter_F Preprocess Algorithm from KEEL.

Usage

```
SaturationFilter_F(train, test, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::SaturationFilter_F(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$preprocessed_test
```

SFS_IEP_FS

SFS_IEP_FS KEEL Preprocess Algorithm

Description

SFS_IEP_FS Preprocess Algorithm from KEEL.

Usage

```
SFS_IEP_FS(train, test, threshold, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
threshold	threshold. Default value = 0.005
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::SFS_IEP_FS(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$preprocessed_test
```

SGA_C

SGA_C KEEL Classification Algorithm

Description

SGA_C Classification Algorithm from KEEL.

Usage

```
SGA_C(train, test, mut_prob_1to0, mut_prob_0to1, cross_prob,
      pop_size, evaluations, alfa, selection_type, k,
      distance, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
mut_prob_1to0	mut_prob_1to0. Default value = 0.01
mut_prob_0to1	mut_prob_0to1. Default value = 0.001
cross_prob	cross_prob. Default value = 1
pop_size	pop_size. Default value = 50
evaluations	evaluations. Default value = 10000
alfa	alfa. Default value = 0.5
selection_type	selection_type. Default value = "orden_based"
k	k. Default value = 1
distance	distance. Default value = "Euclidean"
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::SGA_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

Shrink_C

Shrink_C KEEL Classification Algorithm

Description

Shrink_C Classification Algorithm from KEEL.

Usage

```
Shrink_C(train, test, k, distance)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
k	k. Default value = 1
distance	distance. Default value = "Euclidean"

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::Shrink_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

Slipper_C

Slipper_C KEEL Classification Algorithm

Description

Slipper_C Classification Algorithm from KEEL.

Usage

```
Slipper_C(train, test, grow_pct, numBoosting, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
grow_pct	grow_pct. Default value = 0.66
numBoosting	numBoosting. Default value = 100
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::Slipper_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

SMO_C

SMO_C KEEL Classification Algorithm

Description

SMO_C Classification Algorithm from KEEL.

Usage

```
SMO_C(train, test, C, toleranceParameter, epsilon,
      RBFKernel_gamma, normalized_PolyKernel_exponent,
      normalized_PolyKernel_useLowerOrder, PukKernel_omega,
      PukKernel_sigma, StringKernel_lambda,
      StringKernel_subsequenceLength,
      StringKernel_maxSubsequenceLength, StringKernel_normalize,
      StringKernel_pruning, KernelType, FitLogisticModels,
      ConvertNominalAttributesToBinary, PreprocessType, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
C	C. Default value = 1.0
toleranceParameter	toleranceParameter. Default value = 0.001
epsilon	epsilon. Default value = 1.0e-12
RBFKernel_gamma	RBFKernel_gamma. Default value = 0.01
normalized_PolyKernel_exponent	normalized_PolyKernel_exponent. Default value = 1
normalized_PolyKernel_useLowerOrder	normalized_PolyKernel_useLowerOrder. Default value = FALSE
PukKernel_omega	PukKernel_omega. Default value = 1.0
PukKernel_sigma	PukKernel_sigma. Default value = 1.0
StringKernel_lambda	StringKernel_lambda. Default value = 0.5
StringKernel_subsequenceLength	StringKernel_subsequenceLength. Default value = 3
StringKernel_maxSubsequenceLength	StringKernel_maxSubsequenceLength. Default value = 9
StringKernel_normalize	StringKernel_normalize. Default value = FALSE
StringKernel_pruning	StringKernel_pruning. Default value = "None"
KernelType	KernelType. Default value = "PolyKernel"
FitLogisticModels	FitLogisticModels. Default value = FALSE
ConvertNominalAttributesToBinary	ConvertNominalAttributesToBinary. Default value = TRUE
PreprocessType	PreprocessType. Default value = "Normalize"
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```

data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::SMO_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions

```

SSGA_Integer_knn_FS *SSGA_Integer_knn_FS KEEL Preprocess Algorithm*

Description

SSGA_Integer_knn_FS Preprocess Algorithm from KEEL.

Usage

```

SSGA_Integer_knn_FS(train, test, paramKNN, nEval, pop_size,
  numFeatures, seed)

```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
paramKNN	paramKNN. Default value = 1
nEval	nEval. Default value = 5000
pop_size	pop_size. Default value = 100
numFeatures	numFeatures. Default value = 3
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```

data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::SSGA_Integer_knn_FS(data_train, data_test)
algorithm <- RKEEL::SSGA_Integer_knn_FS(data_train, data_test, nEval = 10, pop_size = 10)

#Run algorithm
algorithm$run()

#See results
algorithm$preprocessed_test

```

Tan_GP_C

Tan_GP_C KEEL Classification Algorithm

Description

Tan_GP_C Classification Algorithm from KEEL.

Usage

```

Tan_GP_C(train, test, population_size, max_generations,
          max_deriv_size, rec_prob, mut_prob, copy_prob, w1, w2,
          elitist_prob, support, seed)

```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
population_size	population_size. Default value = 150
max_generations	max_generations. Default value = 100
max_deriv_size	max_deriv_size. Default value = 20
rec_prob	rec_prob. Default value = 0.8
mut_prob	mut_prob. Default value = 0.1
copy_prob	copy_prob. Default value = 0.01
w1	w1. Default value = 0.7
w2	w2. Default value = 0.8
elitist_prob	elitist_prob. Default value = 0.06
support	support. Default value = 0.03
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::Tan_GP_C(data_train, data_test)
algorithm <- RKEEL::Tan_GP_C(data_train, data_test, population_size = 5, max_generations = 10)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

 Thrift_R

Thrift_R KEEL Regression Algorithm

Description

Thrift_R Regression Algorithm from KEEL.

Usage

```
Thrift_R(train, test, numLabels, popSize, evaluations,
          crossProb, mutProb, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
numLabels	numLabels. Default value = 3
popSize	popSize. Default value = 61
evaluations	evaluations. Default value = 10000
crossProb	crossProb. Default value = 0.6
mutProb	mutProb. Default value = 0.1
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the actual and predicted values for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("autoMPG6_train")
data_test <- RKEEL::loadKeelDataset("autoMPG6_test")

#Create algorithm
algorithm <- RKEEL::Thrift_R(data_train, data_test)
algorithm <- RKEEL::Thrift_R(data_train, data_test, popSize = 5, evaluations = 10)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

UniformFrequency_D *UniformFrequency_D KEEL Preprocess Algorithm*

Description

UniformFrequency_D Preprocess Algorithm from KEEL.

Usage

```
UniformFrequency_D(train, test, numIntervals, seed)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
numIntervals	numIntervals. Default value = 10
seed	Seed for random numbers. If it is not assigned a value, the seed will be a random number

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::UniformFrequency_D(data_train, data_test)

#Run algorithm
algorithm$run()
```

```
#See results
algorithm$preprocessed_test
```

UniformWidth_D

UniformWidth_D KEEL Preprocess Algorithm

Description

UniformWidth_D Preprocess Algorithm from KEEL.

Usage

```
UniformWidth_D(train, test, numIntervals)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
numIntervals	numIntervals. Default value = 10

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::UniformWidth_D(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$preprocessed_test
```

VWFuzzyKNN_C *VWFuzzyKNN_C KEEL Classification Algorithm*

Description

VWFuzzyKNN_C Classification Algorithm from KEEL.

Usage

```
VWFuzzyKNN_C(train, test, k, init_k)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
k	k. Default value = 3
init_k	init_k. Default value = 3

Value

A data.frame with the actual and predicted classes for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("iris_train")
data_test <- RKEEL::loadKeelDataset("iris_test")

#Create algorithm
algorithm <- RKEEL::VWFuzzyKNN_C(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

WM_R *WM_R KEEL Regression Algorithm*

Description

WM_R Regression Algorithm from KEEL.

Usage

```
WM_R(train, test, numlabels, KB)
```

Arguments

train	Train dataset as a data.frame object
test	Test dataset as a data.frame object
numlabels	numlabels. Default value = 5
KB	KB. Default value = FALSE

Value

A data.frame with the actual and predicted values for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("autoMPG6_train")
data_test <- RKEEL::loadKeelDataset("autoMPG6_test")

#Create algorithm
algorithm <- RKEEL::WM_R(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$testPredictions
```

writeDatFromDataframe *Write .dat from data.frame*

Description

Method for writing a .dat dataset file in KEEL format given a data.frame dataset

Usage

```
writeDatFromDataframe(data, fileName)
```

Arguments

data	data.frame dataset
fileName	String with the file name to store the dataset

Examples

```
data(iris)
writeDatFromDataframe(iris, paste0(tempdir(), "/iris.dat"))
```

`writeDatFromDataframes`*Write .dat from data.frames*

Description

Method for writing both train and test .dat dataset files in KEEL format.

Usage

```
writeDatFromDataframes(trainData, testData,  
                        trainFileName, testFileName)
```

Arguments

<code>trainData</code>	Train data as data.frame object
<code>testData</code>	Test data as data.frame object
<code>trainFileName</code>	String with the file name to store the train dataset
<code>testFileName</code>	String with the file name to store the test dataset

`ZScore_TR`*ZScore_TR KEEL Preprocess Algorithm*

Description

ZScore_TR Preprocess Algorithm from KEEL.

Usage

```
ZScore_TR(train, test)
```

Arguments

<code>train</code>	Train dataset as a data.frame object
<code>test</code>	Test dataset as a data.frame object

Value

A data.frame with the preprocessed data for both train and test datasets.

Examples

```
data_train <- RKEEL::loadKeelDataset("car_train")
data_test <- RKEEL::loadKeelDataset("car_test")

#Create algorithm
algorithm <- RKEEL::ZScore_TR(data_train, data_test)

#Run algorithm
algorithm$run()

#See results
algorithm$preprocessed_test
```


Index

* association rules

- Alatasetal_A, 8
- Alcalaetal_A, 12
- Apriori_A, 18
- AssociationRulesAlgorithm, 22
- EARMGA_A, 48
- Eclat_A, 51
- FPgrowth_A, 58
- FuzzyApriori_A, 64
- GAR_A, 72
- GENAR_A, 76
- GeneticFuzzyApriori_A, 83
- GeneticFuzzyAprioriDC_A, 79
- MODENAR_A, 117
- MOEA_Ghosh_A, 121
- MOPNAR_A, 124
- NICGAR_A, 130
- QAR_CIP_NSGAII_A, 150

* classification

- AdaBoost_I, 7
- AdaBoostNC_C, 6
- ART_C, 21
- AssociativeClassificationAlgorithm, 22
- BNGE_C, 23
- Bojarczuk_GP_C, 24
- BSE_C, 25
- C45_C, 28
- C45Binarization_C, 26
- C45Rules_C, 27
- C_SVM_C, 42
- CamNN_C, 29
- CART_C, 29
- CBA_C, 31
- CenterNN_C, 32
- CFAR_C, 32
- CFKNN_C, 33
- CHC_C, 34
- ClassificationAlgorithm, 35

- ClassificationResults, 35
- CMAR_C, 37
- CNN_C, 38
- CPAR_C, 39
- CPW_C, 40
- CW_C, 41
- DecrRBFN_C, 43
- Deeps_C, 44
- DSM_C, 46
- DT_GA_C, 47
- Falco_GP_C, 56
- FCRA_C, 57
- FRNN_C, 61
- FURIA_C, 63
- FuzzyFARCHD_C, 67
- FuzzyKNN_C, 68
- FuzzyNPC_C, 69
- GANN_C, 70
- GFS_AdaBoost_C, 89
- GFS_LogitBoost_C, 93
- ID3_C, 96
- IF_KNN_C, 97
- ImbalancedClassificationAlgorithm, 99
- IncrRBFN_C, 99
- JFKNN_C, 101
- Kernel_C, 102
- KNN_C, 104
- KSNN_C, 105
- KStar_C, 106
- LDA_C, 107
- LinearLMS_C, 108
- Logistic_C, 110
- MLP_BP_C, 114
- NB_C, 129
- NM_C, 133
- NNEP_C, 134
- NU_SVM_C, 136
- PART_C, 138

- PDFC_C, [138](#)
- PFKNN_C, [140](#)
- PNN_C, [140](#)
- PolQuadraticLMS_C, [141](#)
- PRISM_C, [144](#)
- PSO_ACO_C, [146](#)
- PUBLIC_C, [148](#)
- PW_C, [149](#)
- QDA_C, [153](#)
- RBFN_C, [154](#)
- Ripper_C, [158](#)
- RISE_C, [159](#)
- SGA_C, [163](#)
- Shrink_C, [165](#)
- Slipper_C, [165](#)
- SMO_C, [166](#)
- Tan_GP_C, [169](#)
- VWFuzzyKNN_C, [173](#)
- * preprocess**
 - ABB_IEP_FS, [5](#)
 - AllKNN_TSS, [15](#)
 - AllPosible_MV, [16](#)
 - ANR_F, [17](#)
 - Bayesian_D, [23](#)
 - CleanAttributes_TR, [36](#)
 - ClusterAnalysis_D, [36](#)
 - DecimalScaling_TR, [43](#)
 - ID3_D, [96](#)
 - Ignore_MV, [98](#)
 - IterativePartitioningFilter_F, [100](#)
 - KMeans_MV, [103](#)
 - KNN_MV, [104](#)
 - LVF_IEP_FS, [110](#)
 - MinMax_TR, [113](#)
 - ModelCS_TSS, [116](#)
 - MostCommon_MV, [128](#)
 - Nominal2Binary_TR, [135](#)
 - POP_TSS, [143](#)
 - PreprocessAlgorithm, [144](#)
 - Proportional_D, [145](#)
 - PSRCG_TSS, [147](#)
 - Relief_FS, [157](#)
 - SaturationFilter_F, [162](#)
 - SFS_IEP_FS, [163](#)
 - SSGA_Integer_knn_FS, [168](#)
 - UniformFrequency_D, [171](#)
 - UniformWidth_D, [172](#)
 - ZScore_TR, [175](#)
- * regression**
 - CART_R, [30](#)
 - EPSILON_SVR_R, [55](#)
 - FRSBM_R, [62](#)
 - GFS_GP_R, [90](#)
 - GFS_GSP_R, [91](#)
 - GFS_RB_MF_R, [94](#)
 - LinearLMS_R, [108](#)
 - M5_R, [112](#)
 - M5Rules_R, [111](#)
 - MLP_BP_R, [115](#)
 - NU_SVR_R, [137](#)
 - PolQuadraticLMS_R, [142](#)
 - RBFN_R, [155](#)
 - RegressionAlgorithm, [156](#)
 - RegressionResults, [156](#)
 - Thrift_R, [170](#)
 - WM_R, [173](#)
- * utils**
 - downloadFromMirror, [45](#)
 - getAttributeLinesFromDataframes, [87](#)
 - hasContinuousData, [95](#)
 - hasMissingValues, [95](#)
 - isMultiClass, [100](#)
 - loadKeelDataset, [109](#)
 - read.keel, [156](#)
 - runCV, [159](#)
 - runParallel, [160](#)
 - runSequential, [161](#)
 - writeDatFromDataframe, [174](#)
 - writeDatFromDataframes, [175](#)
- ABB_IEP_FS, [5](#)
- AdaBoost_I, [7](#)
- AdaBoostNC_C, [6](#)
- Alatasetal_A, [8](#)
- Alcalaetal_A, [12](#)
- AllKNN_TSS, [15](#)
- AllPosible_MV, [16](#)
- ANR_F, [17](#)
- Apriori_A, [18](#)
- ART_C, [21](#)
- AssociationRulesAlgorithm, [22](#)
- AssociativeClassificationAlgorithm, [22](#)
- Bayesian_D, [23](#)
- BNGE_C, [23](#)
- Bojarczuk_GP_C, [24](#)

- BSE_C, 25

- C45_C, 28
- C45Binarization_C, 26
- C45Rules_C, 27
- C_SVM_C, 42
- CamNN_C, 29
- CART_C, 29
- CART_R, 30
- CBA_C, 31
- CenterNN_C, 32
- CFAR_C, 32
- CFKNN_C, 33
- CHC_C, 34
- ClassificationAlgorithm, 35
- ClassificationResults, 35
- CleanAttributes_TR, 36
- ClusterAnalysis_D, 36
- CMAR_C, 37
- CNN_C, 38
- CPAR_C, 39
- CPW_C, 40
- CW_C, 41

- DecimalScaling_TR, 43
- DecrRBFN_C, 43
- Deeps_C, 44
- downloadFromMirror, 45
- DSM_C, 46
- DT_GA_C, 47

- EARMGA_A, 48
- Eclat_A, 51
- EPSILON_SVR_R, 55

- Falco_GP_C, 56
- FCRA_C, 57
- FPgrowth_A, 58
- FRNN_C, 61
- FRSBM_R, 62
- FURIA_C, 63
- FuzzyApriori_A, 64
- FuzzyFARCHD_C, 67
- FuzzyKNN_C, 68
- FuzzyNPC_C, 69

- GANN_C, 70
- GAR_A, 72
- GENAR_A, 76

- GeneticFuzzyApriori_A, 83
- GeneticFuzzyAprioriDC_A, 79
- getAttributeLinesFromDataframes, 87
- getExePath, 88
- getJarList, 88
- getJarPath, 89
- GFS_AdaBoost_C, 89
- GFS_GP_R, 90
- GFS_GSP_R, 91
- GFS_LogitBoost_C, 93
- GFS_RB_MF_R, 94

- hasContinuousData, 95
- hasMissingValues, 95

- ID3_C, 96
- ID3_D, 96
- IF_KNN_C, 97
- Ignore_MV, 98
- ImbalancedClassificationAlgorithm, 99
- IncrRBFN_C, 99
- isMultiClass, 100
- IterativePartitioningFilter_F, 100

- JFKNN_C, 101

- KeelAlgorithm, 102
- Kernel_C, 102
- KMeans_MV, 103
- KNN_C, 104
- KNN_MV, 104
- KSNN_C, 105
- KStar_C, 106

- LDA_C, 107
- LinearLMS_C, 108
- LinearLMS_R, 108
- loadKeelDataset, 109
- Logistic_C, 110
- LVF_IEP_FS, 110

- M5_R, 112
- M5Rules_R, 111
- MinMax_TR, 113
- MLP_BP_C, 114
- MLP_BP_R, 115
- ModelCS_TSS, 116
- MODENAR_A, 117
- MOEA_Ghosh_A, 121
- MOPNAR_A, 124

- MostCommon_MV, 128
- NB_C, 129
- NICGAR_A, 130
- NM_C, 133
- NNEP_C, 134
- Nominal2Binary_TR, 135
- NU_SVM_C, 136
- NU_SVR_R, 137
- PART_C, 138
- PDFC_C, 138
- PFKNN_C, 140
- PNN_C, 140
- PolQuadraticLMS_C, 141
- PolQuadraticLMS_R, 142
- POP_TSS, 143
- PreprocessAlgorithm, 144
- PRISM_C, 144
- Proportional_D, 145
- PSO_ACO_C, 146
- PSRCG_TSS, 147
- PUBLIC_C, 148
- PW_C, 149
- QAR_CIP_NSgaiI_A, 150
- QDA_C, 153
- R6_ABB_Iep_FS (ABB_Iep_FS), 5
- R6_AdaBoost_I (AdaBoost_I), 7
- R6_AdaBoostNC_C (AdaBoostNC_C), 6
- R6_Alatasetal_A (Alatasetal_A), 8
- R6_Alcalaetal_A (Alcalaetal_A), 12
- R6_AllKNN_TSS (AllKNN_TSS), 15
- R6_AllPosible_MV (AllPosible_MV), 16
- R6_ANR_F (ANR_F), 17
- R6_Apriori_A (Apriori_A), 18
- R6_ART_C (ART_C), 21
- R6_Bayesian_D (Bayesian_D), 23
- R6_BNGE_C (BNGE_C), 23
- R6_Bojarczuk_GP_C (Bojarczuk_GP_C), 24
- R6_BSE_C (BSE_C), 25
- R6_C45_C (C45_C), 28
- R6_C45Binarization_C
(C45Binarization_C), 26
- R6_C45Rules_C (C45Rules_C), 27
- R6_C_SVM_C (C_SVM_C), 42
- R6_CamNN_C (CamNN_C), 29
- R6_CART_C (CART_C), 29
- R6_CART_R (CART_R), 30
- R6_CBA_C (CBA_C), 31
- R6_CenterNN_C (CenterNN_C), 32
- R6_CFar_C (CFAR_C), 32
- R6_CFKNN_C (CFKNN_C), 33
- R6_CHC_C (CHC_C), 34
- R6_CleanAttributes_TR
(CleanAttributes_TR), 36
- R6_ClusterAnalysis_D
(ClusterAnalysis_D), 36
- R6_CMAR_C (CMAR_C), 37
- R6_CNN_C (CNN_C), 38
- R6_CPAR_C (CPAR_C), 39
- R6_CPW_C (CPW_C), 40
- R6_CW_C (CW_C), 41
- R6_DecimalScaling_TR
(DecimalScaling_TR), 43
- R6_DecrRBFN_C (DecrRBFN_C), 43
- R6_Deeps_C (Deeps_C), 44
- R6_DSM_C (DSM_C), 46
- R6_DT_GA_C (DT_GA_C), 47
- R6_EARMGA_A (EARMGA_A), 48
- R6_Eclat_A (Eclat_A), 51
- R6_EPSILON_SVR_R (EPSILON_SVR_R), 55
- R6_Falco_GP_C (Falco_GP_C), 56
- R6_FCRA_C (FCRA_C), 57
- R6_FPgrowth_A (FPgrowth_A), 58
- R6_FRNN_C (FRNN_C), 61
- R6_FRSBM_R (FRSBM_R), 62
- R6_FURIA_C (FURIA_C), 63
- R6_FuzzyApriori_A (FuzzyApriori_A), 64
- R6_FuzzyFARCHD_C (FuzzyFARCHD_C), 67
- R6_FuzzyKNN_C (FuzzyKNN_C), 68
- R6_FuzzyNPC_C (FuzzyNPC_C), 69
- R6_GANN_C (GANN_C), 70
- R6_GAR_A (GAR_A), 72
- R6_GENAR_A (GENAR_A), 76
- R6_GeneticFuzzyApriori_A
(GeneticFuzzyApriori_A), 83
- R6_GeneticFuzzyAprioriDC_A
(GeneticFuzzyAprioriDC_A), 79
- R6_GFS_AdaBoost_C (GFS_AdaBoost_C), 89
- R6_GFS_GP_R (GFS_GP_R), 90
- R6_GFS_GSP_R (GFS_GSP_R), 91
- R6_GFS_LogitBoost_C (GFS_LogitBoost_C),
93
- R6_GFS_RB_MF_R (GFS_RB_MF_R), 94
- R6_ID3_C (ID3_C), 96

- R6_ID3_D (ID3_D), 96
- R6_IF_KNN_C (IF_KNN_C), 97
- R6_Ignore_MV (Ignore_MV), 98
- R6_IncrRBFN_C (IncrRBFN_C), 99
- R6_IterativePartitioningFilter_F
(IterativePartitioningFilter_F),
100
- R6_JFKNN_C (JFKNN_C), 101
- R6_Kernel_C (Kernel_C), 102
- R6_KMeans_MV (KMeans_MV), 103
- R6_KNN_C (KNN_C), 104
- R6_KNN_MV (KNN_MV), 104
- R6_KSNN_C (KSNN_C), 105
- R6_KStar_C (KStar_C), 106
- R6_LDA_C (LDA_C), 107
- R6_LinearLMS_C (LinearLMS_C), 108
- R6_LinearLMS_R (LinearLMS_R), 108
- R6_Logistic_C (Logistic_C), 110
- R6_LVF_IEP_FS (LVF_IEP_FS), 110
- R6_M5_R (M5_R), 112
- R6_M5Rules_R (M5Rules_R), 111
- R6_MinMax_TR (MinMax_TR), 113
- R6_MLP_BP_C (MLP_BP_C), 114
- R6_MLP_BP_R (MLP_BP_R), 115
- R6_ModelCS_TSS (ModelCS_TSS), 116
- R6_MODENAR_A (MODENAR_A), 117
- R6_MOEA_Ghosh_A (MOEA_Ghosh_A), 121
- R6_MOPNAR_A (MOPNAR_A), 124
- R6_MostCommon_MV (MostCommon_MV), 128
- R6_NB_C (NB_C), 129
- R6_NICGAR_A (NICGAR_A), 130
- R6_NM_C (NM_C), 133
- R6_NNEP_C (NNEP_C), 134
- R6_Nominal2Binary_TR
(Nominal2Binary_TR), 135
- R6_NU_SVM_C (NU_SVM_C), 136
- R6_NU_SVR_R (NU_SVR_R), 137
- R6_PART_C (PART_C), 138
- R6_PDFC_C (PDFC_C), 138
- R6_PFKNN_C (PFKNN_C), 140
- R6_PNN_C (PNN_C), 140
- R6_PolQuadraticLMS_C
(PolQuadraticLMS_C), 141
- R6_PolQuadraticLMS_R
(PolQuadraticLMS_R), 142
- R6_POP_TSS (POP_TSS), 143
- R6_PRISM_C (PRISM_C), 144
- R6_Proportional_D (Proportional_D), 145
- R6_PSO_ACO_C (PSO_ACO_C), 146
- R6_PSRCG_TSS (PSRCG_TSS), 147
- R6_PUBLIC_C (PUBLIC_C), 148
- R6_PW_C (PW_C), 149
- R6_QAR_CIP_NSGAII_A (QAR_CIP_NSGAII_A),
150
- R6_QDA_C (QDA_C), 153
- R6_RBFN_C (RBFN_C), 154
- R6_RBFN_R (RBFN_R), 155
- R6_Relief_FS (Relief_FS), 157
- R6_Ripper_C (Ripper_C), 158
- R6_RISE_C (RISE_C), 159
- R6_SaturationFilter_F
(SaturationFilter_F), 162
- R6_SFS_IEP_FS (SFS_IEP_FS), 163
- R6_SGA_C (SGA_C), 163
- R6_Shrink_C (Shrink_C), 165
- R6_Slipper_C (Slipper_C), 165
- R6_SMO_C (SMO_C), 166
- R6_SSGA_Integer_knn_FS
(SSGA_Integer_knn_FS), 168
- R6_Tan_GP_C (Tan_GP_C), 169
- R6_Thrift_R (Thrift_R), 170
- R6_UniformFrequency_D
(UniformFrequency_D), 171
- R6_UniformWidth_D (UniformWidth_D), 172
- R6_VWFuzzyKNN_C (VWFuzzyKNN_C), 173
- R6_WM_R (WM_R), 173
- R6_ZScore_TR (ZScore_TR), 175
- RBFN_C, 154
- RBFN_R, 155
- read.keel, 156
- RegressionAlgorithm, 156
- RegressionResults, 156
- Relief_FS, 157
- Ripper_C, 158
- RISE_C, 159
- runCV, 159
- runParallel, 160
- runSequential, 161
- SaturationFilter_F, 162
- SFS_IEP_FS, 163
- SGA_C, 163
- Shrink_C, 165
- Slipper_C, 165
- SMO_C, 166
- SSGA_Integer_knn_FS, 168

Tan_GP_C, [169](#)

Thrift_R, [170](#)

UniformFrequency_D, [171](#)

UniformWidth_D, [172](#)

VWFuzzyKNN_C, [173](#)

WM_R, [173](#)

writeDatFromDataframe, [174](#)

writeDatFromDataframes, [175](#)

ZScore_TR, [175](#)